

Declaration of Performance

according to Annex III of Regulation (EU) No. 305/2011
LE/DoP No. EGO3150314

1. Identification code of the product type: EGOSILICON 151 SANITÄRPROFI
2. Ident. no.: Batch number: see product packaging
3. Designated use: 1 component silicone sealant, acetate curing
Sealant for facade elements for interior and exterior joints
(suitable for use in cold climate)
Type: F 20 HM EXT-INT-CC
Sealant for glazing
(suitable for use in cold climate)
Type: G 20 HM CC
Sealant for sanitary joints
Type: XS 1
4. Manufacturer: EGO Dichtstoffwerke GmbH & Co. Betriebs KG
Kaltenbrunn 27
82467 Garmisch-Partenkirchen
Germany
5. Authorized representative: ./.
6. System for evaluating reliability of performance: 3 plus 3
7. Harmonized standard: EN 15651-1:2012-12
EN 15651-2:2012-12
EN 15651-3:2012-12
8. Notified body: In its capacity as a notified test laboratory in system 3, ift Rosenheim, NB-No. 0757 carried out the initial tests and issued the test and classification reports.
9. Declared Performance:
Conditioning: Method B
Substrate: Glass without primer



Qualitäts-
Produkte

Type: F 20 HM EXT-INT-CC

Essential characteristics	Performance	Test standard	Harmonized technical specification
Reaction to fire	Class E	EN 13238 (EN 13501)	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD		
Water tightness and air tightness:			
Resistance to flow	≤ 1 mm	EN ISO 7390	
Loss of volume	≤ 5 %	EN ISO 10563	
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF	EN ISO 10590	
Tensile properties (i.e. secant modulus) at -30°C	NR	EN ISO 8339	
Tensile properties (i.e. at maintained extension) at -30°C	NF	EN ISO 8340	
Durability	passed	EN ISO 8339 EN ISO 8340 EN ISO 9047 EN ISO 10590	

NPD = No Performance Determined.
NF = No Failure according to EN ISO 11600.

Type: G 20 HM CC

Essential characteristics	Performance	Test standard	Harmonized technical specification
Reaction to fire	Class E	EN 13238 (EN 13501)	EN 15651-2:2012
Release of chemicals dangerous to the environment and health	NPD		
Water tightness and air tightness:			
Resistance to flow	≤ 1 mm	EN ISO 7390	
Loss of volume	≤ 5 %	EN ISO 10563	



Qualitäts-
Produkte

Essential characteristics	Performance	Test standard	Harmonized technical specification
Adhesion/cohesion properties after exposure to heat water and artificial light	NF	EN ISO 11431	EN 15651-2:2012
Elastic recovery	≥ 90 %	EN ISO 7389	
Tensile properties (i.e. at maintained extension) at -30°C	NF	EN ISO 8340	
Durability	passed	EN ISO 8339 EN ISO 8340 EN ISO 9047 EN ISO 10590	

NPD = No Performance Determined.
NF = No Failure according to EN ISO 11600.

Type: XS1

Essential characteristics	Performance	Test standard	Harmonized technical specification
Reaction to fire	Class E	EN 13238 (EN 13501)	EN 15651-3:2012
Release of chemicals dangerous to the environment and health	NPD		
Water tightness and air tightness:			
Resistance to flow	≤ 1 mm	EN ISO 7390	
Loss of volume	≤ 5 %	EN ISO 10563	
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF	EN ISO 10590	
Microbiological growth	1	ISO 846	
Durability	passed	ISO 846 EN ISO 8339 EN ISO 8340 EN ISO 9047 EN ISO 10590	

NPD = No Performance Determined.
NF = No Failure according to EN ISO 11600.



10. The performance of the product identified in items No. 1 and 2 is in conformity with the declared performance in item No. 9.

This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in item No. 4.

Signed for and on behalf of the manufacturer by:

Garmisch-Partenkirchen, 2 May 2023


Petra Goldmann
Management

The information given in our declaration of performance is based on results obtained under laboratory test conditions. Possible deviations are due to specific conditions in practice that cannot be mapped in the laboratory. Suitable control tests under practical conditions are therefore recommended. Our technical data sheets provide specific material properties as well as advice and recommendations on application. In case of deviations from the application parameters, e. g. other substrates, please contact our technical department who will provide application-related advice. For more information about the safe storage, handling and disposal of the EGO products as well as physical, ecological and other safety-related data please refer to our safety data sheets. All data sheets are available on our website www.ego.de or on request.