

## Declaration of Performance

according to Annex III of Regulation (EU) Nr. 305/2011  
LE/DoP-Nr. EGO4050314

1. Identification code of the product type: EGO SMP 805
2. Ident. no.: Batch number: see product packaging
3. Designated use: 1 component hybrid polymer  
Sealants for facade elements for interior and exterior joints (suitable for use in cold climate)  
Type: F 20 HM EXT-INT-CC  
Sealants for pedestrian walkways for interior and exterior joints (suitable for use in cold climate)  
Type: PW 20 HM EXT-INT-CC
4. Manufacturer: EGO Dichtstoffwerke GmbH & Co. Betriebs KG  
Kaltenbrunn 27  
82467 Garmisch-Partenkirchen  
Germany
5. Authorised representative:./.
6. System for evaluating reliability of performance: 3 plus 3
7. Harmonized standard: EN 15651-1:2012-12  
EN 15651-4:2012-12
8. Notified body: In its capacity as a notified test laboratory in system 3, ift Rosenheim, NR-No. 0757 carried out the initial tests and issued the test and classification reports.
9. Declared Performance:  
Conditioning: Method B  
Substrate: Mortar M1 without primer

Type: F 20 HM EXT-INT-CC

Essential characteristics	Performance	Test standard	Harmonized technical specification
Reaction to fire	Class E	EN 13238 (EN 13501)	EN 15651-1:2012

Essential characteristics	Performance	Test standard	Harmonized technical specification
Release of chemicals dangerous to the environment and health	NPD		
Water tightness and air tightness:			
Resistance to flow	≤ 1 mm	EN ISO 7390	
Loss of volume	≤ 5 %	EN ISO 10563	
Tensile properties at maintained extension after water immersion	NF	EN ISO 10590	
Tensile properties (secant modulus) for use in cold climate areas (-30°C)	NR	EN ISO 8339	
Tensile properties at maintained extension for use in cold climate areas (-30°C)	NF	EN ISO 8340	
Durability	pass	EN ISO 8339 EN ISO 8340 EN ISO 9047 EN ISO 10590	

NPD = No Performance Determined.  
 NF = No Failure according to EN ISO 11600.  
 NR = Not Required.

Type: PW 20 HM EXT-INT-CC

Essential characteristics	Performance	Test standard	Harmonized technical specification
Reaction to fire	Class E	EN 13238 (EN 13501)	EN 15651-4:2012
Release of chemicals dangerous to the environment and health	NPD		
Water tightness and air tightness:			
Resistance to flow	≤ 1 mm	EN ISO 7390	
Loss of volume	≤ 5 %	EN ISO 10563	
Tear resistance	NF	EN ISO 8340	
Adhesion / cohesion properties at maintained extension after 28 days water immersion	NF change of secant modulus ≤ 50 %	EN ISO 10590	
Adhesion / cohesion properties at maintained extension after 28 days salt water immersion	NF	EN ISO 10590	
Tensile properties (secant modulus)	NR	EN ISO 8339	



Essential characteristics	Performance	Test standard	Harmonized technical specification
for use in cold climate areas (-30°C)			
Tensile properties at maintained extension for use in cold climate areas (-30°C)	NF	EN ISO 8340	
Durability	Pass	EN ISO 8339 EN ISO 8340 EN ISO 9047 EN ISO 10590	

10. The performance of the product identified in items No. 1 and 2 is in conformity with the declared performance in item No. 9.

This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in item No. 4.

Signed for and on behalf of the manufacturer by:

Garmisch Partenkirchen, 11 November 2021

*P. Goldmann*  
Petra Goldmann  
Management

The information given in our declaration of performance is based on results obtained under laboratory test conditions. Possible deviations are due to specific conditions in practice that cannot be mapped in the laboratory. Suitable control tests under practical conditions are therefore recommended. Our technical data sheets provide specific material properties as well as advice and recommendations on application. In case of deviations from the application parameters, e. g. other substrates, please contact our technical department who will provide application-related advice. For more information about the safe storage, handling and disposal of the EGO products as well as physical, ecological and other safety-related data please refer to our safety data sheets. All data sheets are available on our website [www.ego.de](http://www.ego.de) or on request.