

according to Regulation (EC) No 1907/2006

### **EGO HAFTREINIGER**

Revision date: 21.04.2023 Product code: 665 Page 1 of 10

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**EGO HAFTREINIGER** 

Product group: Primer

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

### Use of the substance/mixture

contact adhesive/ primer for Silicone Sealant

### 1.3. Details of the supplier of the safety data sheet

Company name: EGO Dichtstoffwerke GmbH & Co. Betriebs KG

Street: Kaltenbrunn 27

Place: D-82467 Garmisch-Partenkirchen

Telephone: +49 (0)8821 956 90 Telefax: +49 (0)8821 956 990

e-mail: info@ego.de

Contact person: Laboratory Telephone: +49 (0)8821 956 960

e-mail: EGO-Labor@ego.de

Internet: www.ego.de

1.4. Emergency telephone +49 55119240 (24h/7d)
number: GIZ-Nord, Göttingen

Member of EPECs network

# **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

# Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

### Regulation (EC) No 1272/2008

## Hazard components for labelling

hydrocarbon, C7-C9, isoalkane

C7-C9 Isoalkane Titantetrabutanolat

toluene

Signal word: Danger

Pictograms:







M - en





Print date: 21.04.2023

### **Hazard statements**

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.



according to Regulation (EC) No 1907/2006

Revision date: 21.04.2023 Product code: 665 Page 2 of 10

H336 May cause drowsiness or dizziness.H411 Toxic to aquatic life with long lasting effects.

### **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P233 Keep container tightly closed.

P243 Take action to prevent static discharges.
P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302+P352 IF ON SKIN: Wash with plenty of water.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P370+P378 In case of fire: Use Extinguishing powder, carbon dioxide (CO2) or alcohol-resistant foam

to extinguish.

P391 Collect spillage.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of contents/container in accordance with local regulation.

## **SECTION 3: Composition/information on ingredients**

# 3.2. Mixtures

#### **Chemical characterization**

silanes and siloxanes with functional groups + auxiliary material in solvent

#### **Hazardous components**

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (Regulation (EC) No	1272/2008)			
	hydrocarbon, C7-C9, isoalkane			< 75 %	
	921-728-3		01-2119471305-42		
	Flam. Liq. 2, Skin Irrit. 2, STOT SE H411	3, Asp. Tox. 1, Aquatic Chronic 2; H	225 H315 H336 H304		
90622-56-3	C7-C9 Isoalkane		< 50 %		
	292-458-5		01-2119471305-42		
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411				
5593-70-4	Titantetrabutanolat		< 5 %		
	227-006-8		01-2119967423-33		
	Flam. Liq. 3, Skin Irrit. 2, Eye Dam.	. 1, STOT SE 3, STOT SE 3; H226 H	315 H318 H335 H336		
108-88-3	toluene		< 5 %		
	203-625-9	601-021-00-3			
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H225 H361d H315 H336 H373 H304				

Full text of H and EUH statements: see section 16.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

#### **EGO HAFTREINIGER**

Revision date: 21.04.2023 Product code: 665 Page 3 of 10

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. L	imits, M-factors and ATE		
	921-728-3	hydrocarbon, C7-C9, isoalkane	< 75 %	
	inhalation: LC5	0 = 21 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg		
90622-56-3	292-458-5	C7-C9 Isoalkane	< 50 %	
	inhalation: LC50 = 21 mg/l (vapours); dermal: LD50 = > 3000 mg/kg; oral: LD50 = > 10000 mg/kg			
108-88-3	203-625-9	toluene	< 5 %	
	inhalation: LC5	0 = 49 mg/l (vapours); dermal: LD50 = 12200 mg/kg		

### **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

#### After inhalation

Move to fresh air in case of accidental inhalation of vapours. If you feel unwell, seek medical advice (show the label where possible).

If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice.

### After contact with skin

Wash off with soap and water. Take off all contaminated clothing immediately.

#### After contact with eyes

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

# After ingestion

Do NOT induce vomiting. Danger of inhalation Show this safety data sheet to the doctor in attendance.

## 4.2. Most important symptoms and effects, both acute and delayed

This information is not available.

# 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Further information on toxicology in Section 11 should be noted.

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

# Suitable extinguishing media

Dry powder, Carbon dioxide (CO2), alcohol resistant foam.

# Unsuitable extinguishing media

High volume water jet

# 5.2. Special hazards arising from the substance or mixture

Combustion may provoke smoke emission.

Vapours may form explosive mixtures with air.

### 5.3. Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

#### **Additional information**

Standard procedure for chemical fires.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Use personal protective equipment. Do not breathe vapours or spray mist. Ensure adequate ventilation, especially in confined areas. Avoid contact with skin and eyes.

Remove all sources of ignition. Do not smoke.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

#### **EGO HAFTREINIGER**

Revision date: 21.04.2023 Product code: 665 Page 4 of 10

Take precautionary measures against static discharges.

#### For non-emergency personnel

Remove from all sources of ignition. Provide adequate ventilation. Wear personal protection equipment.

#### For emergency responders

Wear personal protection equipment.

#### 6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. When leaking into waters, sewers or underground, notify competent authority.

# 6.3. Methods and material for containment and cleaning up

#### For containment

Cover the sewers.

### For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Use mechanical handling equipment.

#### Other information

Treat recovered material as described in the section "Disposal considerations".

#### 6.4. Reference to other sections

See also section 7,8,13

### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

### Advice on safe handling

Provide sufficient air exchange and/or exhaust in work rooms.

## Advice on protection against fire and explosion

Take measures to prevent the build up of electrostatic charge.

Processing may lead to evolution of flammable volatiles. Vapours may form explosive mixtures with air.

Keep away from sources of ignition - No smoking.

# Advice on general occupational hygiene

Handle in accordance with good industrial hygiene and safety practice.

When using, do not eat, drink or smoke. Do not breathe vapours or spray mist. Avoid contact with the skin and the eyes. Take off all contaminated clothing immediately. Wash contaminated clothing before re-use. Wash hands before breaks and at the end of workday.

#### Further information on handling

Avoid prolonged or repeated contact with skin.

## 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep containers tightly closed in a dry, cool and well-ventilated place.

Keep away from direct sunlight. Keep away from heat and sources of ignition.

## Hints on joint storage

None known.

# Further information on storage conditions

Keep containers dry and tightly closed to avoid moisture absorption and contamination.

### 7.3. Specific end use(s)

contact adhesive/ primer for Silicone Sealant

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters



according to Regulation (EC) No 1907/2006

### **EGO HAFTREINIGER**

Revision date: 21.04.2023 Product code: 665 Page 5 of 10

### Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m³	fib/cm³	Category	Origin
108-88-3	Toluene	50	192		TWA (8 h)	
		100	384		STEL (15 min)	

### **DNEL/DMEL values**

CAS No	Name of agent				
DNEL type	DNEL type		Effect	Value	
	hydrocarbon, C7-C9, isoalkane				
Consumer DN	EL, long-term	oral	systemic	699 mg/kg bw/day	
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day	
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day	
Consumer DNEL, long-term		inhalation	systemic	608 mg/m³	
Worker DNEL, long-term		inhalation	systemic	2035 mg/m³	

### 8.2. Exposure controls

# Individual protection measures, such as personal protective equipment

# Eye/face protection

Tightly fitting safety goggles

#### Hand protection

Solvent-resistant gloves: Fluorinated rubber, NBR (Nitrile rubber).

The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Request information on glove permeation properties from the glove supplier. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

### Skin protection

Protective suit

# Respiratory protection

Ensure adequate ventilation, especially in confined areas. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. (gas filter type ABEK / ABEK-P2). In case of long or strong exposure, use breathing apparatus. Suitable respiratory protection: Self-contained breathing apparatus, according to recognized standards such as EN 137.

### Thermal hazards

Do not heat the product.

Under fire conditions: Flame-resistant clothing Low temperature resistant gloves: not required

# **Environmental exposure controls**

Do not flush into surface water or sanitary sewer system.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: colourless
Odour: characteristic

Melting point/freezing point:

Boiling point or initial boiling point and

90 - 150 °C

boiling range:

Lower explosion limits: 0,9 vol. %

not applicable



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

### **EGO HAFTREINIGER**

Revision date: 21.04.2023 Product code: 665 Page 6 of 10

Upper explosion limits: 7,0 vol. %
Flash point: 3 °C
Auto-ignition temperature: > 200 °C
Water solubility: insoluble
Vapour pressure: not determined
(at 20 °C)
Density (at 20 °C): 0,74 g/cm³

SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reaction known under conditions of normal use.

# 10.2. Chemical stability

Particle characteristics:

Stable under normal conditions.

#### 10.4. Conditions to avoid

Heat, flames and sparks. humid air and water.

# 10.5. Incompatible materials

Oxidizing agents, Acids, Bases, Water.

# 10.6. Hazardous decomposition products

No decomposition if used as directed.

# **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

# **Acute toxicity**

No data is available on the product itself.

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
	hydrocarbon, C7-C9, isoa	alkane				
	oral	LD50 mg/kg	>5000	rat		
	dermal	LD50 mg/kg	>2000	rat		
	inhalation (4 h) vapour	LC50	21 mg/l	rat		
90622-56-3	C7-C9 Isoalkane					
	oral	LD50 mg/kg	> 10000	rat		
	dermal	LD50 mg/kg	> 3000	rat		
	inhalation (4 h) vapour	LC50	21 mg/l	rat		
108-88-3	toluene					
	dermal	LD50 mg/kg	12200	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50	49 mg/l	Rat	GESTIS	

### Irritation and corrosivity

Irritating to respiratory system and skin.

# Sensitising effects

None known.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

#### **EGO HAFTREINIGER**

Revision date: 21.04.2023 Product code: 665 Page 7 of 10

### Carcinogenic/mutagenic/toxic effects for reproduction

No data is available on the product itself.

### STOT-single exposure

Vapours may cause drowsiness and dizziness.

#### STOT-repeated exposure

No data is available on the product itself.

#### **Aspiration hazard**

Risk of serious damage to the lungs (by aspiration). Aspiration may cause pulmonary oedema and pneumonitis.

### Information on likely routes of exposure

Skin contact

#### 11.2. Information on other hazards

### **Further information**

Harmful by inhalation and in contact with skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Concentration above the admissible concentration at the workplace may cause dizziness, headache and inebriation.

# **SECTION 12: Ecological information**

### 12.1. Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
	hydrocarbon, C7-C9, iso	alkane					
	Algae toxicity	NOEC	6,3 mg/l	3 d			
	Crustacea toxicity	NOEC mg/l	0,17	21 d			
108-88-3	toluene						
	Acute fish toxicity	LC50	13 mg/l	96 h	Carassius auratus	IUCLID	
	Acute algae toxicity	ErC50 mg/l	12,5	72 h		GESTIS	

# 12.2. Persistence and degradability

no data available

# 12.3. Bioaccumulative potential

Bioaccumulation is unlikely.

# Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-88-3	toluene	2,73

### 12.4. Mobility in soil

no data available

# 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).

This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

### **EGO HAFTREINIGER**

Revision date: 21.04.2023 Product code: 665 Page 8 of 10

no data available

# **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

## **Disposal recommendations**

Can be incinerated, when in compliance with local regulations.

Do not put residues of product into household waste. It should be given in the original package to the official waste disposal authorities.

### Contaminated packaging

Empty remaining contents. Dispose of in accordance with local regulations.

# **SECTION 14: Transport information**

Land transport (ADR/RID)

14.1. UN number or ID number: UN 3295

14.2. UN proper shipping name: HYDROCARBONS, LIQUID, N.O.S. (contains isoparaffins, C7-C9

isoalkanes)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1
Special Provisions: 640D
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Tunnel restriction code: D/E

Marine transport (IMDG)

14.1. UN number or ID number: UN 3295

14.2. UN proper shipping name: HYDROCARBONS, LIQUID, N.O.S.

(contains isoparaffins, C7-C9 isoalkanes)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Marine pollutant: yes
Special Provisions: Limited quantity: 1 L
EmS: F-E, S-D

Other applicable information (marine transport)

E2

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3295

14.2. UN proper shipping name: HYDROCARBONS, LIQUID, N.O.S.

(contains isoparaffins, C7-C9 isoalkanes)

M - en

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



according to Regulation (EC) No 1907/2006

# **EGO HAFTREINIGER**

Revision date: 21.04.2023 Product code: 665 Page 9 of 10



Special Provisions: A3 A224 Limited quantity Passenger: 1 L

IATA-packing instructions - Passenger:353IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

Other applicable information (air transport)

Y341 E2

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Print date: 21.04.2023

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 48

2004/42/EC (VOC): VOC(EU) 91,5% VOC(CH) 91,5%

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

# **SECTION 16: Other information**

### Changes

This data sheet contains changes from the previous version in section(s): 1,6,7,8,9,11,16.

# Abbreviations and acronyms

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

**UN: United Nations** 

CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LC50: Lethal concentration, 50%

LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50%



according to Regulation (EC) No 1907/2006

# **EGO HAFTREINIGER**

Revision date: 21.04.2023 Product code: 665 Page 10 of 10

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation

intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules MFAG: Medical First Aid Guide

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container VOC: Volatile Organic Compounds SVHC: Substance of Very High Concern

# Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Chronic 2; H411	Calculation method

### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

#### **Further Information**

These data describe only the safety requirements for the product(s) and are based on our present knowledge. However, they do not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)