

# **EGO GEWÄCHSHAUSKITT**

is a high quality, softplastic, gunnable putty that is free from asbestos, bitumen, tar, plasticisers, mineral oils and solvents. High quality raw materials guarantee its permanently plastic properties and excellent adhesion to glass, metal, paints etc. EGO Greenhouse Putty is stable in volume, easy to apply, does not tend to form cracks and prevents water from penetrating into the joint.

### **TYPICAL USES**

Simple and low-budget glazing of greenhouses and industrial buildings, sealing of glass roofs.

### **APPLICATION**

Apply **EGO** Greenhouse Putty only onto dry and clean profiles that are free from substances liable to impair adhesion. Make sure the external joint has a cross-section of at least 20 x 20 mm. **EGO** Greenhouse Putty forms a skin after about 3 days and does not have to be over-painted. **EGO** Greenhouse Putty is not compatible with bituminous substrates.



### **TECHNICAL DATA**

Properties	Result
Density	approx. 1.9 g/cm <sup>3</sup>
Application Temperature	+ 5° c to + 30° C
Service Temperature	approx 30° C to + 80° C
Consistency	softplastic
Method of Application	with EGOFIX Compressed Air Gun
Rework	with dampened tool
Secondary Treatment	Smooth carefully with a moist tool. We recommend to over-paint the putty with a weatherproof paint once it has formed a solid skin.

## **AVAILABILITY AND STORAGE**

Standardfarbe	dark brown
Packaging	70 mm Ø foil bags, 15 kg/box
	50 mm Ø foil bags, 10 kg/box
	25 kg bucket
	Special packaging upon requsted.
Storage	Store in cool and dry conditions in closed original
	packaging. Shelf life 12 months











Dichtstoffe e. V. (IVD)



### **SAFETY INSTRUCTIONS**

Meets Requirements of	REACH Regulation (EC) No. 1907/2006
Not hazardous	According to EC No. 1272/2008 (CLP)
Not subject to Labelling	According to EC No. 1272/2008 (CLP)
Safety Guidelines	See EC safety data sheet
Disposal	See EC safety data sheet

Precautions see EC Security Data Sheet. The above specifications are the result of careful research and development. All previous specifications are hereby null and void. Users are them selves responsible for ensuring the suitability of the product for the purpose intended, liability on the part of EGO being limited to the purchase price of the material. EGO cannot accept liability for damage, in particular that caused by the use of the product or its unsuitability, nor can EGO accept responsibility for unauthorized recommendations or guarantees which deviate from or exceed the specifications given in this product data sheet.

EGO Dichtstoffwerke GmbH & Co. Betriebs KG • Kaltenbrunn 27 • D-82467 Garmisch-Partenkirchen

Member of the Industrieverband Dichtstoffe e. V. (IVD)





www.ego.de