

## EGO GLÄTTMITTEL

is a fluid, colourless, eudermic smoothing agent for all kinds of substrates.

### TYPICAL USES

Suited for silicone, polyurethane, MS polymer and acrylic sealants.

### APPLICATION

Apply sparingly onto the joint surface and remove spilled smoothing agent immediately – do not allow the product to dry.

In case of sensitive substrates (wood, rough or absorbant substrates etc.), mask the adjoining areas with adhesive tape.

For natural stone please use **EGO** Stone Tooling Agent for Stone Silicone.

### TECHNICAL DATA

Properties	Result
Dosage Standard Smoothing Agent	Can be diluted with clear water, mixing ratio 1:4 to max 1:5
Dosage Tooling Agent (Concentrate)	Can be diluted with clear water, mixing ratio 1:100 (use three caps of concentrate for 1L water)
Compatibility	Free from tensides and substances that may discolour the selant
pH Value	Approx. 7

### AVAILABILITY AND STORAGE

Colour	Colourless
Packaging	500ml can 5L can 200L drum
Storage	store in cool and dry conditions in original, unopened packaging. Shelf life 12 months

### SAFETY INSTRUCTIONS

Meets Requirements of	REACH Regulation (EC) No. 1907/2006 and No. 1272/2008 CLP
Labelling	See EC safety data sheet
Safety Guidelines	See EC safety data sheet
Disposal	See EC safety data sheet

Precautions see EC Security Data Sheet. The above specifications are the result of careful research and development. All previous specifications are hereby null and void. Users are them selves responsible for ensuring the suitability of the product for the purpose intended, liability on the part of EGO being limited to the purchase price of the material. EGO cannot accept liability for damage, in particular that caused by the use of the product or its unsuitability, nor can EGO accept responsibility for unauthorized recommendations or guarantees which deviate from or exceed the specifications given in this product data sheet.