



FOAM SEALANT STRIPS

EGOPREN C1



- Fire resistant acc. to DIN 4102 (B1)

EGOPREN C1 is a precompressed, impregnated polyurethane soft foam sealant strip that is self-adhesive on one side, meets the requirements of DIN 18542-BG1 and is fire resistant according to DIN 4102 (general building inspection test certificate available).

The product is supplied in rolls. After positioning the material expands gradually according to temperature and adapts to the width of the joint and to uneven surfaces.

EGOPREN C1 is resistant to weathering, UV radiation and driving rain acc. to DIN 18055, water vapour permeable, waterproof as well as paint compatible. It is free from CFC and chlorinated substances.

For sealing exterior wall joints in the building construction, the construction of prefabricated concrete elements, for timber, masonry, metal, as perimeter seal around doors and windows as well as for sealing roofs, conservatories and ventilation systems.

In accordance with IVD Instruction Sheets No. 9, 19-1, 19-2, 20, 24, 26, 28, 29, 31, 35

(IVD = German Sealant Manufacturers' Association)

EGOPREN C1

Size delivered	Width/ Roll mm	For Joint Width mm	Roll Length m	Rolls/ Box	Colour Black Article No.
10/2-3	10	2-3	12,5	11	611021082 *
15/2-3	15	2-3	12,5	7	611021582 *
20/2-3	20	2-3	12,5	5	611022082 *
10/3-5	10	3-5	10	11	611031082 *
15/3-5	15	3-5	10	7	611031582 *
20/3-5	20	3-5	10	5	611032082 *
10/4-7	10	4-7	8	11	611041082
15/4-7	15	4-7	8	7	611041582 *
20/4-7	20	4-7	8	5	611042082 *
25/4-7	25	4-7	8	4	611042582 *
30/4-7	30	4-7	8	3	611043082 *
10/5-10	10	5-10	5,6	11	611051082 *
15/5-10	15	5-10	5,6	7	611061582 *
20/5-10	20	5-10	5,6	5	611062082 *
20/7-12	20	7-12	4,3	5	611082082 *
25/7-12	25	7-12	4,3	4	611072582 *
30/7-12	30	7-12	4,3	3	611073082 *
20/8-15	20	8-15	3,3	5	611102082 *
25/8-15	25	8-15	3,3	4	611082582 *
30/8-15	30	8-15	3,3	3	611083082
25/10-18	25	10-18	6,5	12	611102582
30/10-18	30	10-18	6,5	10	611103082 *

* Minimum order quantity on request.

Special dimensions on request.

EGO External Window Membrane



- Water vapour permeable
- Rainproof
- Easy to install
- Self-adhesive
- Supplied in rolls

EGO External Window Membrane

Standard Sizes Width	Rolls/Box	Colour	Article No.
70 mm	5 x 40 m	White	612070070
100 mm	3 x 40 m	White	612100070
150 mm	2 x 40 m	White	612150070

EGO External Window Membrane consists of a water vapour permeable PES-PE-PES laminate with self-adhesive strip for fast and reliable sealing of external window perimeter joints.

In accordance with IVD Instruction Sheets No. 9, 29, 35
(IVD = German Sealant Manufacturers' Association)

EGOPREN C2



- Normally flammable acc. to DIN 4102 (B2)

EGOPREN C2 is a precompressed, impregnated polyurethane soft foam sealant strip that is self-adhesive on one side, meets the requirements of DIN 18542 BG2 and is normally flammable (B2) acc. to DIN 4102 (general building inspection test certificate available). The product is supplied in rolls. After positioning the material expands gradually according to temperature and adapts to the width of the joint and to uneven surfaces.

EGOPREN C2 is resistant to weathering, UV radiation and driving rain acc. to DIN 18055, water vapour permeable, waterproof as well as paint compatible. It is free from CFC and chlorinated substances.

Perimeter seal around windows, doors and thermal insulation composite systems, for the construction of prefabricated parts, timber construction, interior work, container manufacture, masonry, metal construction. Especially suited for sealing water vapour permeable external perimeter joints around windows and doors as well as for sealing roofs, conservatories and ventilation systems.

In accordance with IVD Instruction Sheets No. 9, 19-1, 19-2, 20, 24, 26, 28, 29, 31, 35
(IVD = German Sealant Manufacturers' Association)

EGOPREN C2

Size delivered	Width/ Roll mm	For Joint Width mm	Roll Length m	Rolls/ Box	Colour Black Article No.
10/2-3	10	2-3	12,5	11	604021082
15/2-3	15	2-3	12,5	7	604021582 *
20/2-3	20	2-3	12,5	5	604022082 *
10/3-5	10	3-5	10	11	604031082
15/3-5	15	3-5	10	7	604031582
20/3-5	20	3-5	10	5	604032082
10/4-7	10	4-7	8	11	604041082
15/4-7	15	4-7	8	7	604041582
20/4-7	20	4-7	8	5	604042082 *
25/4-7	25	4-7	8	4	604042582 *
30/4-7	30	4-7	8	3	604043082
10/5-10	10	5-10	5,6	11	604051082
15/5-10	15	5-10	5,6	7	604061582
20/5-10	20	5-10	5,6	5	604062082
20/7-12	20	7-12	4,3	5	604082082
25/7-12	25	7-12	4,3	4	604072582
30/7-12	30	7-12	4,3	3	604073082
20/8-15	20	8-15	3,3	5	604102082
25/8-15	25	8-15	3,3	4	604082582 *
30/8-15	30	8-15	3,3	3	604083082 *
25/10-18	25	10-18	6,5	12	604102582
30/10-18	30	10-18	6,5	10	604103082 *

* Minimum order quantity on request.

Special dimensions on request.

EGO Internal Window Membrane



- Water vapour retardant
- Airtight
- Easy to install
- Self-adhesive
- Supplied in rolls

EGO Internal Window Membrane

Standard Sizes Width	Rolls/Box	Colour	Article No.
70 mm	5 x 40 m	Red	612070071
100 mm	3 x 40 m	Red	612100071
150 mm	2 x 40 m	Red	612150071

EGO Internal Window Membrane consists of a water vapour proof PES-PE-PES laminate with self-adhesive strip for fast and reliable sealing of internal window perimeter joints.

In accordance with IVD Instruction Sheets No. 9, 29, 35
(IVD = German Sealant Manufacturers' Association)

GLAZING TAPES

EGOPREN Foam Sealant Strip



EGOPREN is a closed-cell PE foam sealant strip that is self-adhesive on one side and supplied with a PE film. It is thread reinforced, plasticiser-free and weatherproof. EGOPREN serves as spacing element for single and double glazing to be sealed after the tape has been installed as well as for parapet elements.

Packaging:

2, 3, 4 mm thickness: 5 rolls of 20 m shrink wrapped

5 mm thickness: 5 rolls of 10 m shrink wrapped
1500 m/box

**In accordance with IVD Instruction Sheet No. 10
(IVD = German Sealant Manufacturers' Association)**

EGOPREN Foam Sealant Strip

Standard Sizes Thickness x Width	Black Article No.	White Article No.
2 x 6 mm	606060280	-
2 x 8 mm	606080280	606080210
2 x 9 mm	606090280	606090210
2 x 10 mm	606100280	606100210
2 x 12 mm	606120280	-
2 x 15 mm	606150280	-
3 x 6 mm	606060380	-
3 x 8 mm	606080380	606080310
3 x 9 mm	606090380	606090310
3 x 10 mm	606100380	606100310
3 x 12 mm	606120380	606120310
3 x 15 mm	606150380	-
4 x 8 mm	606080480	606080410
4 x 9 mm	606090480	606090410
4 x 10 mm	606100480	-
4 x 12 mm	606120480	-
5 x 9 mm	606090580	606090510
5 x 10 mm	606100580	-
5 x 12 mm	606120580	-

EGOPREN S Foam Sealant Strip



EGOPREN S is a closed-cell PE foam sealant strip that is self-adhesive on one side and supplied without release film. It is thread reinforced, plasticiser-free and weatherproof.

Especially suited as spacing element for single and double glazing to be sealed after the tape has been installed as well as for parapet elements.

EGOPREN S Foam Sealant Strip

Standard Sizes Thickness x Width	Black Article No.	White Article No.
2 x 6 mm	609060280	-
2 x 8 mm	609080280	-
2 x 9 mm	609090280	609090210
2 x 10 mm	609100280	609100210
2 x 12 mm	609120280	-
3 x 8 mm	609080380	609080310
3 x 9 mm	609090380	609090310
3 x 10 mm	609100380	609100310
3 x 12 mm	609120380	609120310
4 x 9 mm	609090480	609090410
4 x 10 mm	609100480	-
4 x 12 mm	609120480	-
5 x 9 mm	609090580	-
5 x 10 mm	609100580	-

Packaging:

2, 3, 4 mm thickness: 5 rolls of 20 m shrink wrapped

5 mm thickness: 5 rolls of 10 m shrink wrapped
1500 m/box

**In accordance with IVD Instruction Sheet No. 10
(IVD = German Sealant Manufacturers' Association)**

EGO PE Joint Backing Rod



EGO PE Joint Backing Rod

Diametre	Packaging	Metres/Box	Grey Article No.
40 mm	Rods of 2 m length	270 m	603040072
50 mm	Rods of 2 m length	180 m	603050072
6 mm	100 m reels	500 m	603006073
8 mm	100 m reels	500 m	603008073
10 mm	100 m reels	500 m	603010073
13 mm	100 m reels	500 m	603013073
15 mm	100 m reels	500 m	603015073
20 mm	50 m reels	250 m	603020073
25 mm	50 m reels	250 m	603025073
30 mm	25 m reels	125 m	603030073

EGO PE Joint Backing Rod is a closed-cell, weatherproof, plasticiser-free PE foam joint backing rod according to DIN 18540 for perimeter and construction joints.

EGO PUR Joint Backing Rod



EGO PUR Joint Backing Rod

Diametre	Metres/Box	Grey Article No.
10 mm	1500 m	602010004
15 mm	1000 m	602015004
20 mm	500 m	602020004
25 mm	350 m	602025004
30 mm	250 m	602030004
40 mm	150 m	602040004
50 mm	100 m	602050004

EGO PUR Joint Backing Rod is an open-cell polyurethane joint backing rod for connecting joints. Does not meet the requirements of DIN 18540, fire protection classification B3.



JOINT BACKING RODS



EGO FIBERFRAX		
Standard Sizes Thickness x Width	Metres/Box	White Article No.
3 x 8 mm	350 m	600080310
3 x 10 mm	300 m	600100310
3 x 12 mm	250 m	600120310
3 x 15 mm	200 m	600150310
3 x 20 mm	150 m	600200310
3 x 23 mm	100 m	600230310
4 x 15 mm	200 m	600150410
4 x 20 mm	150 m	600200410
5 x 12 mm	250 m	600120510
5 x 15 mm	200 m	600150510
5 x 20 mm	150 m	600200510
6 x 15 mm	200 m	600150610

EGO FIBERFRAX is a ceramic fibre joint sealant strip that is non-flammable acc. to DIN 4102. It is chemically neutral, environment-friendly and not harmful. In case of fire EGO FIBERFRAX does not develop smoke gas and does not drip material when exposed to flames. EGO FIBERFRAX is free from asbestos.

For fire-resistant and fire-retardant glazing as well as for joints that require a B1 seal according to DIN 4102.

**In accordance with IVD Instruction Sheets No. 11, 29
(IVD = German Sealant Manufacturers' Association)**