

EGOTAPE 2000 ALUMINIUM SEALING TAPE

is a self-adhesive, aluminium-coated, thermoplastic, butyl rubber-based sealing tape. The lamination consists of a tear-resistant aluminium foil that is permanently bonded to the butyl. The aluminium sealing tape offers high radon and water vapour diffusion impermeability. In addition, it can be used as a universal sealing tape in the construction sector. With its properties and components, the aluminium sealing tape is excellently suited as a joint tape in the field of „sustainable building“ and has been verified according to the DGNB, LEED, BREEAM and BNB rating systems.

CHARACTERISTICS

This combination results in optimal properties:

self-adhesive on one side · easy processing · immediately functional even without primer · resistant to ageing, weathering, UV and long-term use · smooth aluminium coloured foil surface · mechanical armouring · no bimetal effect · radon-proof according to G. Keller · solvent- and bitumen-free · physiologically harmless · odourless · noise-insulating · water-proof and -resistant · high water vapour diffusion impermeability · non-corrosive · has an insulating effect · bitumen-compatible · plastic · non-shrinking · good adhesion and compatibility with most known materials · when used properly and professionally, EGO Butyl has an almost unlimited service life

APPLICATION AREAS

EGOTAPE 2000 is suitable for simple and permanent sealing of construction and connection joints. The aluminium sealing tape is basically suitable as universal sealing tape in the construction sector as well as for example as repair tape in the caravan sector.

Areas of application:

connections to windows & doors · connections between canopy & masonry · concrete construction · prefabricated concrete construction · roof openings · greenhouses · skylight domes · pitched roof glass constructions [with pressure profile] · butt joints made of glass, plastic or metal · conservatories

APPLICATION NOTES

The bonding surfaces must be dry, stable, free of dust and de-bonding agents. On porous substrates such as concrete, plaster, etc., adhesion can be increased by pre-treatment with **EGO BUTYLPRIMER PRO** or **EGO BUTYLPRIMER ECO** [solvent-free]. For increased adhesion, please refer to the primer table. The adhesion build-up on the substrate is purely physical and can be improved by pressing or rolling on the substrate or increases again automatically over time. The temperature behaviour is typically thermoplastic, i.e. with increasing temperature, a higher stickiness with simultaneously softer material consistency is achieved. Cross laying in the roof area should be avoided as there is a risk of being pushed off by snow and ice loads. The adhesive surface of the sealing tape must be at least 20 mm on both sides of the joint [gap] for joint overlays on smooth, non-absorbent substrates and at least 30 mm on porous, absorbent substrates. The necessary pressure is applied with a pressure roller. Avoid folds and creases and roll out with care. For the professional, crease-free installation of **EGOTAPE 2000**, a video is available on our homepage. Simply dab off butyl residues on the substrates or tools with butyl. Impurities that are difficult to dissolve can be removed mechanically, e.g. with a sharp knife moistened with water, and are best dissolved with cleaning petrol.

Compatibility with other building materials is only guaranteed with the EGO products recommended for this.

Our list of material properties provides you with an overview of all the necessary information and a detailed comparison of our EGO BUTYL products.

NORMS AND TESTS

EGOTAPE 2000 corresponds to the:

IVD Instruction Sheets:

- No. 5, 19-1, 19-2, 24, 25, 29, 31

Compatibility:

- with bitumen in accordance with DIN EN 1548
- Radon tightness [determination of the radon diffusion coefficient and the diffusion length of 1 mm thick **EGOTAPE 2000**]

SUSTAINABILITY

VOC emission according to:

- EMICODE EC1^{Plus}
- AgBB
- French VOC Class A+ and CMR-Regulation

BMS product verifications:

- LEED Building Design and Construction V4 [2015]
- BNB BN 2015 [quality level 5/5]
- BREEAM International New Construction 2016
- DGNB New Buildings 2018 [quality level 4]

Listing in baubook:

- **EGOTAPE 2000** is listed in baubook

Listing in the DGNB Navigator:

- **EGOTAPE 2000** is listed in the DGNB Navigator

Material requirements for QNG / Quality Seal for Sustainable Buildings:

- Adhesives and sealants in interior rooms incl. TGA according to BNB_BN_11.6, Annex 1, Item 8 and QNG-313, Items 4.1, 4.2
- Adhesives and sealants for creating the airtightness of the façade in accordance with BNB_BN_11.6, Annex 1, Item 9 and QNG-313, Item 4.3

EGOTAPE 2000 ALUMINIUM SEALING TAPE

SUSTAINABILITY



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ [très faibles émissions] à C [fortes émissions]

TECHNICAL DATA

Product-Properties	Result	in accordance with
Material Basis sealant	butyl rubber, polyisobutylene [PIB]	
Material Basis film	aluminium/plastic film	
Application Temperature	+5°C to 30°C	
Service Temperature	-40°C to +100°C	
Viscosity	stable	DIN EN ISO 7390
Solids Content	> 99 %	DIN EN ISO 10563
μ - Value	minimum 1200000	DIN EN ISO 12572
Sd-Value	Sd = μ x d	d = tape thickness in [m]
Radon diffusion length	L = 0,48 mm [d = 1,00 mm > 3L]	ISO/TS 11665-13

Butyl-Properties	Result	in accordance with
Density	approx. 1,4g/cm³	DIN EN ISO 1183-1
Shore Hardness 00	approx. 45	DIN EN ISO 868
Compressive Strength	> 0,08 N/mm²	LAB-01 [based on NF P30-303]
Penetration butyl [150g, 23°C, 5sec]	approx. 70 [0,1mm]* Butyl 30x30mm	DIN 51580
Peel strength butyl	approx. 45 N/mm²	LAB-06 [based on DIN EN 29862]
UV, weather and long-term resistance of butyl [after 1000 hrs]	very good no crack formation no breaking no reduction of the tack	DIN EN ISO 4892-2:2013
Bending resistance of butyl [after 100 hrs at +90°C & 5 hrs at -30°C]	No crack formation No breaking	
Building material class	B2, normal flammability Euro class E	DIN 4102 EN 13501-1

* Average values, not intended for specification

AVAILABILITY AND STORAGE

Standard Color Butyl	grey			
Standard Color Film	grey			
Standard Dimensions	Thickness x Width	Meters/Roll	Rolls/Box	Meters/Box
	0,9 x 40 mm	25	8	200
	0,9 x 50 mm	25	6	150
	0,9 x 60 mm	25	6	150
	0,9 x 80 mm	25	4	100
	0,9 x 100 mm	25	2	50
	0,9 x 150 mm	25	2	50

EGOTAPE 2000 ALUMINIUM SEALING TAPE

AVAILABILITY AND STORAGE

Standard Dimensions

Thickness x Width	Meters/Roll	Rolls/Box	Meters/Box
1,5 x 35 mm	25	8	200
1,5 x 40 mm	25	8	200
1,5 x 45 mm	25	6	150
1,5 x 50 mm	25	6	150
1,5 x 60 mm	25	6	150
1,5 x 80 mm	25	4	100
1,5 x 100 mm	25	2	50
1,5 x 120 mm	25	2	50
1,5 x 150 mm	25	2	50
1,5 x 200 mm	25	2	50

Special sizes on request.

Storage

Rolls can be stored horizontally, dry and protected from dust:
 ■ 24 months [at +20°C]
 Protect against mechanical damage.

SAFETY INFORMATION

Complies with	Regulation [EC] No 1907/2006 [REACH]
Not hazardous according to	Regulation [EC] No 1272/2008 [CLP]
Not subject to labeling according to	Regulation [EC] No 1272/2008 [CLP]
Safety instructions	see SDS
Disposal instructions	see SDS

For warnings see EC safety data sheet. The above information is the result of thorough research; previous information is hereby invalidated. Check for yourself whether the product is suitable for your purposes. Our possible liability is limited to the value of our product as such. We cannot accept any liability for indirect damage, in particular for the use or unusability of the product. No one is authorized to make recommendations or assurances on our behalf that go beyond the content of our information sheets.