

EGOSILICON 360

 0757	
EGO Dichtstoffwerke 14 EG03360314	
EN 15651-1 EN 15651-2 EN 15651-3 EN 15651-4 1 component silicone sealant, neutral curing Sealant for facade elements for interior and exterior joints Sealant for glazing Sealant for sanitary joints Sealants for pedestrian walkways for interior and exterior joints (suitable for use in cold climate) F 25 LM EXT-INT-CC G 25 LM CC XS1 PW 25 LM EXT-INT-CC Conditioning: Method B Substrate: Glass without primer Mortar M1 with EGO PRIMER FDF	
Reaction to fire	Class E
Release of chemicals dangerous to the environment and health	evaluated
Water tightness and air tightness:	
Resistance to flow	≤ 1 mm
Loss of volume	≤ 10 %
Tensile properties (i.e. elongation) at maintained extension after water immersion	passed
Tensile properties (i.e. secant modulus) for low modulus sealants at -30 °C	≤ 0,9 MPa
Tensile properties (i.e. at maintained extension) at -30 °C	passed
Adhesion/cohesion properties after exposure to	passed

heat water and artificial light	
Adhesion/elongation behavior under preload after immersion in salt water after 28 days	passed
Adhesion/cohesion properties at variable temperatures	passed
Tear resistance	passed
Elastic recovery	≥ 90 %
Microbiological growth	0
Durability	passed