

Product Verification

Sustainability

Product Systems

EGO SMP 805

EGO Dichtstoffwerke GmbH & Co. Betriebs KG

EGO SMP 805 is a single-component, odourless adhesive & sealant that cures with the humidity in the air to form an elastic end product. It does not contain solvents, is free from silicone and isocyanate and provides high resistance against chemicals. For bonding and sealing in the field of construction and industry, for both indoor and outdoor applications, e.g. in metal, roof, camper van and concrete construction. Sealing for elastic connection joints in buildings and pedestrian paths. Can also be used on plaster, gypsum, ceramics, timber, glass, enamel, zinc, lead, stainless steel, HPL high-pressure laminates, hard PVC, aluminium, galvanised sheet metal, fibre-reinforced cement and various plastic substrates. Well suited for bonding of construction foils, rails/strips and panels. If to be used with porous natural stone or some types of plastics, such as PA, PS, EPDM, please perform your own application-related tests and trials or consult us. EGO SMP 805 fulfills the requirements according to EMICODE EC 1 PLUS.

<https://www.ego.de/produkt/egosmp805>



■ Ecolabels & Product-Assessments

AgBB tested



EMICODE

EMICODE EC1plus



EPD



EPD Institut Bauen und
Umwelt e.V.



French VOC-Label A+



ISO 14001 - Environmental
Management System



ISO 9001 - Quality
Management System



SCAQMD 1168



■ Product Properties

Ingredients:

Percentage of the product's composition, that is known to the chemical ingredient level	100 wt%
SVHC according REACH < 0,1 %:	Yes
Free (< 0,1 %) of chlorinated paraffins (= CP inkl. SCCP, MCCP, LCCP):	Yes
Content of solvents:	0 %
Free (< 0,1 %) of hydrocarbon (KWS) plasticizer:	Yes
Free (< 0,1 %) of polybrominated diphenyl ethers (= PBDE):	Yes
Free (< 0,1 %) of biocidal:	Yes
VOC content according 2004/42/EG:	0 g/l
VOC content according 2004/42/EG:	0 g/m2
Recycled content pre-consumer:	N/A
Recycled content post-consumer:	N/A
To what level of detail is the product composition known?	100 ppm
Rapidly renewable content	N/A
Non renewable virgin raw material content	N/A

Free (< 0,1 %) of polybrominated biphenyls (= PBB):	Yes
Free (< 0,1 %) of hexabromocyclododecane (= HBCD):	Yes
Free (< 0,1 %) of tris (2-carboxyethyl) phosphine (= TCEP):	Yes
Free (< 0,1 %) of lead:	Yes
Free (< 0,1 %) of cadmium:	Yes
Free (< 0,1 %) of chromium-VI compounds:	Yes
Free of solvent according to VdL-RL01:	Yes
Free (< 0,1 %) of aromatic compounds:	Yes
Free (< 0,1 %) from halogenated propellants:	Yes
Free (< 0,1 %) of halogenated flame retardants:	Yes
Content of VOC:	0 %
Free (< 0,1 %) of halogens:	Yes
Free of plasticizer according to VdL-RL01:	Yes

Manufacturer:

Environmental Management System according ISO 14001:	Yes
Final manufacturing location of the product: latitude	47,4902251743193 ° DDD
Final manufacturing location of the product: longitude	11,177539584701767 ° DDD

Emissions:

Formaldehyde emissions after 28 days according DIN EN 717-1:	0,002 mg/m ³
Carcinogens 1A and 1B after 28 days according ISO-16000 / AgBB:	0,001 mg/m ³
R-Value according to AgBB:	0,00
TVOC after 3 days according ISO 16000-3 / AgBB:	0,005 mg/m ³
TVOC after 28 days according ISO 16000-3 / AgBB:	0,005 mg/m ³
SVOC after 3 days according ISO 16000-3 / AgBB:	0,005 mg/m ³
SVOC after 28 days according ISO 16000-3 / AgBB:	0,005 mg/m ³
Carcinogens 1A and 1B after 3 days according ISO-16000 / AgBB:	0,001 mg/m ³

Life Cycle Assessment:

Functional use period	N/A
-----------------------	-----

Circularity:

Other:

test

N/A

■ Contact Details Manufacturer

EGO Dichtstoffwerke GmbH & Co. Betriebs KG

Kaltenbrunn 27
82467 Garmisch-Partenkirchen
DE
<http://www.ego.de/>



■ Disclaimer

Notice: This verification is generated by the Assessment Service of BMS. The distribution or publication by third parties is not permitted. The information is based on the manufacturer's specifications. Despite a diligent treatment of all information BMS can not make any warranties about the completeness, reliability and accuracy of this information. The user of the data sheet, the user / purchaser of the product and the consultant / planner, who is advising on this product has the duty to check the product for the intended application at their own responsibility. When a new version of this product verification is produced, the previous version loses its validity.