

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

CONLOC SK 711

Revision: 15.12.2025

Product code: 750711030

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

CONLOC SK 711

Product group: silicone

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Silicone Sealant/adhesive

1.3. Details of the supplier of the safety data sheet

| | | |
|-----------------|--|--------------------------------|
| Company name: | EGO Dichtstoffwerke GmbH & Co. Betriebs KG | |
| Street: | Kaltenbrunn 27 | |
| Place: | D-82467 Garmisch-Partenkirchen | |
| Telephone: | +49 (0)8821 956 90 | Telefax: +49 (0)8821 956 990 |
| E-mail: | info@ego.de | |
| Contact person: | Laboratory | Telephone: +49 (0)8821 956 960 |
| E-mail: | EGO-Labor@ego.de | |
| Internet: | www.ego.de | |

1.4. Emergency telephone number:

+49 55119240 (24h/7d)
GIZ-Nord, Göttingen
Member of EPECs network

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Flam. Liq. 2; H225
Skin Irrit. 2; H315
Eye Irrit. 2; H319
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008**

Signal word: Danger

Pictograms:

**Hazard statements**

| | |
|------|--|
| H225 | Highly flammable liquid and vapour. |
| H315 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |
| H412 | Harmful to aquatic life with long lasting effects. |

Precautionary statements

| | |
|------|--|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P233 | Keep container tightly closed. |
| P243 | Take action to prevent static discharges. |
| P273 | Avoid release to the environment. |
| P280 | Wear protective gloves / protective clothing / eye protection. |

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

CONLOC SK 711

Revision: 15.12.2025

Product code: 750711030

Page 2 of 11

| | |
|----------------|--|
| P302+P352 | IF ON SKIN: Wash with plenty of water and soap. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P314 | Get medical advice/attention if you feel unwell. |
| P501 | Dispose of contents/container in accordance with local regulation. |

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Polydimethylsiloxane + curing agents + fillers + auxiliary agents

Relevant ingredients

| CAS No | Chemical name | Quantity | | |
|------------|--|--------------|------------------|---------|
| | EC No | Index No | REACH No | |
| | Classification (Regulation (EC) No 1272/2008) | | | |
| 68909-20-6 | silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica | | | < 25 % |
| | 272-697-1 | 014-052-00-7 | | |
| | STOT RE 2; H373 EUH066 | | | |
| 90622-56-3 | C7-C9 Isoalkane | | | < 20 % |
| | 292-458-5 | | 01-2119471305-42 | |
| | Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411 | | | |
| 4253-34-3 | Methyltriacetoxysilan | | | < 10 % |
| | 224-221-9 | | 01-2119962266-32 | |
| | Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1; H302 H314 H318 EUH014 | | | |
| 1067-33-0 | Dibutylzinndiacetat | | | < 0.1 % |
| | 213-928-8 | | 01-2119634587-29 | |
| | Muta. 2, Repr. 1B, Skin Corr. 1B, Skin Sens. 1B, STOT SE 1, STOT RE 1, Aquatic Chronic 1; H341 H360 H314 H317 H370 H372 H410 | | | |
| 556-67-2 | octamethylcyclotetrasiloxane; [D4] | | | < 0.1 % |
| | 209-136-7 | 014-018-00-1 | | |
| | Repr. 2, Aquatic Chronic 1; H361f H410 | | | |

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

| CAS No | EC No | Chemical name | Quantity | |
|------------|---|------------------------------------|----------|--|
| | Specific Conc. Limits, M-factors and ATE | | | |
| 90622-56-3 | 292-458-5 | C7-C9 Isoalkane | < 20 % | |
| | inhalation: LC50 = 21 mg/l (vapours); dermal: LD50 = > 3000 mg/kg; oral: LD50 = > 10000 mg/kg | | | |
| 4253-34-3 | 224-221-9 | Methyltriacetoxysilan | < 10 % | |
| | oral: ATE = 500 mg/kg | | | |
| 1067-33-0 | 213-928-8 | Dibutylzinndiacetat | < 0.1 % | |
| | Aquatic Chronic 1; H410: M=10 | | | |
| 556-67-2 | 209-136-7 | octamethylcyclotetrasiloxane; [D4] | < 0.1 % | |
| | Aquatic Chronic 1; H410: M=10 | | | |

Further Information

This product does not contain any reportable Eu-listed Substances of Very High Concern (SVHC) in a

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

CONLOC SK 711

Revision: 15.12.2025

Product code: 750711030

Page 3 of 11

concentration of $\geq 0,1\%$ (Regulation (EC) No 1907/2006 (REACH), Article 59)**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

During polymerization the product releases small quantities of acetic acid.
In case of accident or if you feel unwell, seek medical advice immediately (show the packaging, label or safety data sheet if possible).
Do not leave the injured person unattended.

After inhalation

Provide fresh air. Keep patient warm and at rest.

After contact with skin

Take off immediately all contaminated clothing After contact with skin, wash immediately with plenty of water and soap. If skin irritation persists, call a physician.

After contact with eyes

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Get medical attention.

After ingestion

If victim is conscious: Let water be swallowed in little sips (dilution effect). Do not induce vomiting. Get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Relevant information can be found in other parts of this section.

4.3. Indication of any immediate medical attention and special treatment needed

Further information on toxicology in Section 11 should be noted.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water fog. alcohol resistant foam. Carbon dioxide. Extinguishing powder. Sand.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire hazardous combustion gases or vapors possible. Exposure to combustion products can be a health hazard! Hazardous fire products: toxic and very toxic fumes.

5.3. Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Use a tight-fitting chemical protective suit. Keep unprotected people away.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Wear personal protection equipment. Avoid contact with skin and eyes. Do not breathe gas/vapour. Special skid risk by leaking/spilling product. Keep unprotected people away. Provide adequate ventilation.

For non-emergency personnel

Remove from all sources of ignition. Provide adequate ventilation. Wear personal protection equipment.

For emergency responders

Wear personal protection equipment.

6.2. Environmental precautions

Do not empty into drains or the aquatic environment. Contain spillage, and then collect with non-combustible

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

CONLOC SK 711

Revision: 15.12.2025

Product code: 750711030

Page 4 of 11

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see section 13).

Retain and dispose of contaminated wash water.

6.3. Methods and material for containment and cleaning up**For containment**

Cover the sewers.

For cleaning up

Pick up mechanically and dispose of properly. Do not rinse with water. For small quantities: Take up with liquid-binding preferably acid-binding material and dispose of properly. For large quantities: Liquids can be taken up with suction devices or pumps. If flammable, use only air-powered or properly-regulated electrical appliances. Remove any remaining slippery surface with detergent / soap solution or other biodegradable cleaner. Silicone oils are slippery, spilled substance is therefore a safety hazard. To improve the grip, apply sand or other inert, granular material.

Other information

Vacuum off vapors. Provide adequate ventilation. Remove from all sources of ignition. Observe Ex protection.

6.4. Reference to other sections

See also section 8,13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Provide sufficient air exchange and/or exhaust in work rooms. Vapors / aerosols must be cleaned by suction at the place of origin.

Advice on protection against fire and explosion

Fumes may form explosive mixtures with air. Keep product and empty container away from heat and sources of ignition. Take precautionary measures against static discharges.
Cool closed containers exposed to fire with water spray.

Advice on general occupational hygiene

Avoid contact with the skin and the eyes. Do not breathe gas/fumes/vapour/spray. When using, do not eat, drink or smoke. Keep working clothes separately.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

This information is not available.

Hints on joint storage

This information is not available.

Further information on storage conditions

Protect from moisture. Keep in a dry, cool and well-ventilated place.
Minimum storage temperature: 0 °C

7.3. Specific end use(s)

Silicone Sealant/adhesive

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limit values**

| CAS No | Name of agent | ppm | mg/m ³ | fib/cm ³ | Category | Origin |
|---------|---------------|-----|-------------------|---------------------|---------------|--------|
| 64-19-7 | Acetic acid | 10 | 25 | | TWA (8 h) | |
| | | 20 | 50 | | STEL (15 min) | |

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

CONLOC SK 711

Revision: 15.12.2025

Product code: 750711030

Page 5 of 11

8.2. Exposure controls**Individual protection measures, such as personal protective equipment****Eye/face protection**

Tightly sealed safety glasses.

Hand protection

Protective gloves Fluorinated rubber.

Duration of use approx. 480 minutes. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Skin protection

Protective suit

Respiratory protection

If inhalation exposure above the workplace exposure limit can not be excluded, appropriate respiratory protective equipment should be used. Suitable respiratory protection: Respirator with full face mask, in accordance with recognized standards such as EN 136. Recommended filter type: ABEK gas filter (certain inorganic, organic and acid gases and vapors, ammonia / amines), in accordance with recognized standards such as EN 14387 Wear appropriate respiratory protective equipment and protective clothing when exposed to spray or aerosol. Suitable respiratory protection: Respirator with full face mask, in accordance with recognized standards such as EN 136. Recommended filter type: Combination filter ABEK-P2 (certain inorganic, organic and acid gases and vapors, ammonia / amines, particles), according to recognized standards such as EN 14387 In case of long or strong exposure, use breathing apparatus. Suitable respiratory protection: Self-contained breathing apparatus, according to recognized standards such as EN 137. The wearing time limit for respiratory protection as well as instructions of the device manufacturer are to be observed.

Thermal hazards

Do not heat the product.

Under fire conditions: Flame-resistant clothing

Low temperature resistant gloves: not required

Environmental exposure controls

Do not empty into drains or the aquatic environment.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| | |
|------------------|----------------|
| Physical state: | liquid |
| Colour: | transparent |
| Odour: | vinegar-like |
| Odour threshold: | not determined |

| | Test method |
|---|--|
| Melting point/freezing point: | Exempt |
| Boiling point or initial boiling point and boiling range: | 111 °C |
| Lower explosion limits: | 1,2 vol. % |
| Upper explosion limits: | 7 vol. % |
| Flash point: | 14 °C ISO 3679 |
| Auto-ignition temperature: | 412 °C DIN EN ISO/IEC 80079-20-1 |
| pH-Value: | not applicable, Mixture not soluble in water |
| Water solubility: | virtually insoluble |

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

CONLOC SK 711

Revision: 15.12.2025

Product code: 750711030

Page 6 of 11

Vapour pressure: 29 hPa
(at 20 °C)
Density (at 23 °C): approx. 1,05 g/cm³ DIN EN ISO 2811
Particle characteristics: not applicable

9.2. Other information**Other safety characteristics**

Viscosity / dynamic: approx. 65000 mPa·s Brookfield
(at 23 °C)

Further Information

Possible decomposition products in case of hydrolysis are:
acetic acid: explosion limits 4 -17 Vol-%

SECTION 10: Stability and reactivity**10.1. Reactivity**

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable at normal ambient temperature and pressure.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

moisture. Heat, flames and sparks.

10.5. Incompatible materials

Reacts with water, Bases, alcohols. Formation of: Acetic acid.

10.6. Hazardous decomposition products

Possible decomposition products in case of hydrolysis are: Acetic acid.

Further information

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

No toxicology information is available.
Acute toxicity estimate (Oral) >2000 mg/kg

ATEmix calculated

ATE (oral) > 5000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

| CAS No | Chemical name | | | | |
|------------|-------------------------|--------------------|---------|--------|--------|
| | Exposure route | Dose | Species | Source | Method |
| 90622-56-3 | C7-C9 Isoalkane | | | | |
| | oral | LD50 > 10000 mg/kg | rat | | |
| | dermal | LD50 > 3000 mg/kg | rat | | |
| | inhalation (4 h) vapour | LC50 21 mg/l | rat | | |
| 4253-34-3 | Methyltriacetoxysilan | | | | |
| | oral | ATE 500 mg/kg | | | |

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

CONLOC SK 711

Revision: 15.12.2025

Product code: 750711030

Page 7 of 11

Irritation and corrosivity

Irritating to eyes and skin.
(Result, Methods of detection and analysis rabbit)

Sensitising effects

No data is available on the product itself.

Carcinogenic/mutagenic/toxic effects for reproduction

No data is available on the product itself.

STOT-single exposure

No data is available on the product itself.

STOT-repeated exposure

No data is available on the product itself.

Aspiration hazard

Due to the viscosity, this product does not present an aspiration hazard.

Information on likely routes of exposure

Skin contact

11.2. Information on other hazards**Further information**

During polymerization the product releases small quantities of acetic acid. Do not inhale highly-concentrated release products for a longer period of time during polymerization, danger of irritation.

SECTION 12: Ecological information**12.1. Toxicity**

There are no test data for the complete mixture.

12.2. Persistence and degradability

Polymer component Not biodegradable.
The product can be eliminated from water by abiotic processes, e.g. adsorption on activated sludge.

12.3. Bioaccumulative potential

Polymer component Bioaccumulation is unlikely.

12.4. Mobility in soil

Polymer component none Water solubility

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

None known.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Recommendation: Material that can not be recycled, reprocessed or recycled should be disposed of in an approved facility in accordance with national, state and local regulations. Depending on the regulations, waste treatment methods may include, for example, disposal in a landfill or incineration.
For this product, no waste code number according to the European Waste Catalog (AVV) can be specified, since only the intended use by the consumer allows an allocation. The waste code number must be determined within the EU in consultation with the disposal company.

Contaminated packaging

Packaging must be completely emptied (drip-free, free from trickle, spatula-clean). Packaging must preferably

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONLOC SK 711

Revision: 15.12.2025

Product code: 750711030

Page 8 of 11

be reused or recycled in compliance with the applicable local / national regulations.
Non-cleanable packaging must be disposed of in the same way as the substance.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (C7-C9 isoalkanes, n-propanol)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Special Provisions: 274 601
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Marine transport (IMDG)

14.1. UN number or ID number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (C7-C9 Isoalkanes, n-Propanol)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Marine pollutant: no
Special Provisions: 274
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-E

Other applicable information (marine transport)

Special provisions: 274, 330, 944

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (C7-C9 Isoalkanes, n-Propanol)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: A3
Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2
IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

CONLOC SK 711

Revision: 15.12.2025

Product code: 750711030

Page 9 of 11

IATA-packing instructions - Cargo: 364

IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

road transport: Dangerous goods - exemption of limited quantities (3.4 ADR / RID)!

rail transport: Dangerous goods - exemption of limited quantities (3.4 ADR / RID)!

Sea Freight: LIMITED QUANTITY according to 3.4 IMDG code possible up to 30 kg gross per package (composite packaging).

14.7. Maritime transport in bulk according to IMO instruments

There is no intended bulk transport in tankers.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):

octamethylcyclotetrasiloxane; [D4]

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 30, Entry 40, Entry 75

Additional information

Moreover, national legislation has to be obeyed!

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Additional information

Chemicals Prohibition Ordinance (ChemVerbotsV): This product is not subject to the Chemicals Prohibition Ordinance when placed on the market in Germany.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1,2,4,5,6,7,8,9,11,12,13,14,15,16.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

CONLOC SK 711

Revision: 15.12.2025

Product code: 750711030

Page 10 of 11

Abbreviations and acronyms

Flam. Liq. 2: Flammable liquids, hazard category 2
Acute Tox. 4: Acute toxicity, hazard category 4
Asp. Tox. 1: Aspiration hazard, hazard category 1
Skin Corr. 1B: Skin corrosion, sub-category 1B
Skin Irrit. 2: Skin irritation, hazard category 2
Eye Dam. 1: Serious eye damage, hazard category 1
Eye Irrit. 2: Eye irritation, hazard category 2
Skin Sens. 1B: Skin sensitisation, hazard category 1B
Muta. 2: Germ cell mutagenicity, hazard category 2
Repr. 1B: Reproductive toxicity, hazard category 1B
STOT SE 1: Specific target organ toxicity - single exposure, hazard category 1
STOT RE 1: Specific target organ toxicity - repeated exposure, hazard category 1
Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard category: Chronic 1
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
IMDG: International Maritime Code for Dangerous Goods
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds
SVHC: Substance of Very High Concern

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

| Classification | Classification procedure |
|-------------------------|--------------------------|
| Flam. Liq. 2; H225 | On basis of test data |
| Skin Irrit. 2; H315 | |
| Eye Irrit. 2; H319 | |
| Aquatic Chronic 3; H412 | |

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

CONLOC SK 711

Revision: 15.12.2025

Product code: 750711030

Page 11 of 11

Relevant H and EUH statements (number and full text)

| | |
|--------|--|
| H225 | Highly flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H336 | May cause drowsiness or dizziness. |
| H341 | Suspected of causing genetic defects. |
| H360 | May damage fertility or the unborn child. |
| H361f | Suspected of damaging fertility. |
| H370 | Causes damage to organs. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |
| EUH014 | Reacts violently with water. |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |

Further Information

These data describe only the safety requirements for the product(s) and are based on our present knowledge. However, they do not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)