

according to Regulation (EC) No 1907/2006

# **CONLOC UV 665 FARBIG**

Revision date: 03.05.2023

Product code: 740665613

Page 1 of 12

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

CONLOC UV 665 FARBIG

Product group:

Adhesives

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

## Use of the substance/mixture

UV curing adhesive

#### 1.3. Details of the supplier of the safety data sheet

Company name:	EGO Dichtstoffwerke GmbH & Co. Be	triebs KG
Street:	Kaltenbrunn 27	
Place:	D-82467 Garmisch-Partenkirchen	
Telephone: e-mail:	+49 (0)8821 956 90 info@ego.de	Telefax:+49 (0)8821 956 990
Contact person: e-mail: Internet:	Laboratory EGO-Labor@ego.de www.ego.de	Telephone: +49 (0)8821 956 960
<u>1.4. Emergency telephone</u> number:	+49 55119240 (24h/7d) GIZ-Nord, Göttingen Member of EPECs network	

# **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

## Regulation (EC) No 1272/2008

Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 STOT SE 3; H335 Aquatic Acute 1; H400 Aquatic Chronic 1; H410

Full text of hazard statements: see SECTION 16.

## 2.2. Label elements

#### Regulation (EC) No 1272/2008

#### Hazard components for labelling

Isobornyl acrylate 2-hydroxyethyl methacrylate Acrylsäure maleic acid tert-Butylperbenzoat

Signal word: Pictograms: Danger



#### Hazard statements

H315	
H317	
H318	

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage.



according to Regulation (EC) No 1907/2006

# **CONLOC UV 665 FARBIG**

Revision date: 03.05.2023	Product code: 740665613	Page 2 of 12
H335	May cause respiratory irritation.	
H410	Very toxic to aquatic life with long lasting effects.	
Precautionary statemer	nts	
P261	Avoid breathing Vapor / spray.	
P273	Avoid release to the environment.	
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.	
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P310	Immediately call a POISON CENTER/doctor.	

# 2.3. Other hazards

Do not expose skin and above all eyes to direct or reflected UV light during curing.

# **SECTION 3: Composition/information on ingredients**

# 3.2. Mixtures

#### Chemical characterization

Mixture of substances listed below with nonhazardous additions.

## Hazardous components

CAS No	Chemical name	Quantity				
	EC No	Index No	REACH No			
	Classification (Regulation (EC)					
5888-33-5	Isobornyl acrylate			< 50 %		
	227-561-6					
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1B, STOT SE 3, Aquatic Acute 1, Aquatic Chronic 1; H315 H319 H317 H335 H400 H410					
868-77-9	2-hydroxyethyl methacrylate			< 25 %		
	212-782-2	607-124-00-X				
	Skin Irrit. 2, Eye Irrit. 2, Skin Se	ns. 1; H315 H319 H317	•			
7473-98-5	2-Hydroxy-2-methylpropiophen	< 5 %				
	231-272-0					
	Acute Tox. 4, Aquatic Chronic 3					
79-10-7	Acrylsäure	< 5 %				
	201-177-9		01-2119452449-31			
	Flam. Liq. 3, Acute Tox. 4, Acut Aquatic Acute 1, Aquatic Chron					
614-45-9	tert-Butylperbenzoat	< 1 %				
	210-382-2					
	Self-react. C, Acute Tox. 4, Skin H400					
110-16-7	maleic acid	< 1 %				
	203-742-5	607-095-00-3				
	Acute Tox. 4, Skin Irrit. 2, Eye I					

Full text of H and EUH statements: see section 16.



according to Regulation (EC) No 1907/2006

# **CONLOC UV 665 FARBIG**

Revision date: 03.05.2023

Product code: 740665613

Page 3 of 12

# Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
5888-33-5	227-561-6	Isobornyl acrylate	< 50 %
	dermal: LD50	= > 3000 mg/kg; oral: LD50 = 4350 mg/kg	
868-77-9	212-782-2	2-hydroxyethyl methacrylate	< 25 %
	oral: LD50 = 5	050 mg/kg	
7473-98-5	231-272-0	2-Hydroxy-2-methylpropiophenone	< 5 %
	dermal: LD50	= 6929 mg/kg; oral: LD50 = 1694 mg/kg	
79-10-7	201-177-9	Acrylsäure	< 5 %
		50 = >5,1 mg/l (vapours); inhalation:  ATE = 1,5 mg/l (dusts or mists); dermal: j/kg; oral:  LD50 = 1500 mg/kg	
614-45-9	210-382-2	tert-Butylperbenzoat	< 1 %
	inhalation: ATE 1012 mg/kg	E = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: LD50 =	
110-16-7	203-742-5	maleic acid	< 1 %
	oral: ATE = 50	0 mg/kg Skin Sens. 1; H317: >= 0,1 - 100	

#### **Further Information**

For the full text of the H-Statements mentioned in this Section, see Section 16.

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### General information

Take off all contaminated clothing immediately. First aider needs to protect himself. Show this safety data sheet to the doctor in attendance.

#### After inhalation

Move to fresh air in case of accidental inhalation of vapours. Consult physician if problems persist. If victim is at risk of losing consciousness, position and transport on their side.

#### After contact with skin

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

#### After contact with eyes

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

#### After ingestion

Consult a physician. Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting.

## 4.2. Most important symptoms and effects, both acute and delayed

No information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

If swallowed with subsequent vomiting, aspiration into the lungs may occur, resulting in chemical pneumonia or asphyxiation.

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

#### Suitable extinguishing media

Dry powder, Foam, Carbon dioxide (CO2).

Extinguishing materials should be selected according to the surrounding area.

## Unsuitable extinguishing media

High volume water jet



according to Regulation (EC) No 1907/2006

# **CONLOC UV 665 FARBIG**

Revision date: 03.05.2023

Product code: 740665613

Page 4 of 12

# 5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

## 5.3. Advice for firefighters

In the event of fire and/or explosion do not breathe fumes. In the event of fire, wear self-contained breathing apparatus.

#### Additional information

Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

## **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Ensure adequate ventilation. Do not breath vapour. Wear personal protection equipment. Avoid contact with skin, eye and clothing.

#### For non-emergency personnel

Remove from all sources of ignition. Provide adequate ventilation. Wear personal protection equipment.

#### For emergency responders

Wear personal protection equipment.

## 6.2. Environmental precautions

Prevent allover extension (e.g.knocking-down or a boom). Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3. Methods and material for containment and cleaning up

# For containment

Cover the sewers.

#### For cleaning up

Small amounts: Wipe up with absorbent material (e.g. cloth, fleece). Substantial quantities: Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the assimilated material according to the section on waste disposal.

# Other information

Provide adequate ventilation.

## 6.4. Reference to other sections

See also section 7, 8, 13

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice.

Avoid contact with skin and eyes. Provide sufficient air exchange and/or exhaust in work rooms. Keep away from direct sunlight. Avoid the formation of aerosol.

#### Advice on protection against fire and explosion

Keep away from heat.

#### Advice on general occupational hygiene

Handle in accordance with good industrial hygiene and safety practice.

Avoid contact with skin. Avoid contact with eyes. Do not breath vapour.

Wash hands when done working with material; at breaks, lunch, shift changes, etc. Take off immediately all contaminated clothing

When using, do not eat, drink or smoke. Keep away from food, drink and animal feedingstuffs.



according to Regulation (EC) No 1907/2006

# **CONLOC UV 665 FARBIG**

Revision date: 03.05.2023

Product code: 740665613

Page 5 of 12

## 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep tightly closed in a dry and cool place. Protect against light. Never return unused material to storage receptacle.

# Hints on joint storage

not required under normal use

# 7.3. Specific end use(s)

Adhesives

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m³	fib/cm³	Category	Origin
79-10-7	Acrylic acid; Prop-2-enoic acid	10	29		TWA (8 h)	
		20	59		STEL (1 min)	

## Additional advice on limit values

2-Hydroxyethylmethacrylat

MAK see chapter IIb

#### 8.2. Exposure controls

#### Appropriate engineering controls

Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Do not expose skin and above all eyes to direct or reflected UV light during curing.

## Individual protection measures, such as personal protective equipment

## Eye/face protection

Safety glasses with side-shields.

## Hand protection

Protective gloves: Glove material Nitrile rubber (>= 0,4 mm) Break through time > 8h.

As the product is a mixture of several substances, the durability of the glove materials cannot be calculated in advance and has to be tested before use.

Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.

# Skin protection

Long sleeved clothing

## **Respiratory protection**

Ensure adequate ventilation, especially in confined areas.

In case of insufficient ventilation wear suitable respiratory equipment.

For short-term or low-load respiratory filter device (filter A); in case of intensive or prolonged exposure use self-contained breathing apparatus

#### Thermal hazards

Do not heat the product. Under fire conditions: Flame-resistant clothing Low temperature resistant gloves: not required



according to Regulation (EC) No 1907/2006

# **CONLOC UV 665 FARBIG**

Revision date: 03.05.2023

Product code: 740665613

Page 6 of 12

#### **Environmental exposure controls**

Do not allow material to contaminate ground water system.

## **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

	a enemiear properties	
Physical state:	liquid	
Colour:	various	
Odour:	characteristic	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point a	nd	not determined
boiling range:		
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		>100 °C
pH-Value:		not determined
Water solubility:		insoluble
Density:		approx. 1,1 g/cm <sup>3</sup>
Particle characteristics:		not applicable
9.2. Other information		
Information with regard to physic	al hazard classes	
Explosive properties		

The product is: not Explosive.

#### Other safety characteristics

Solvent content:	0 %
Viscosity / dynamic:	approx. 100 mPa·s
(at 20 °C)	

## Further Information

The product is: not auto-flammable

#### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2. Chemical stability

No decomposition if used as directed.

#### 10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

# 10.4. Conditions to avoid

Exposure to light.

# 10.5. Incompatible materials

None known.

#### 10.6. Hazardous decomposition products

irritating gases / vapors

## **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

No data is available on the product itself.



according to Regulation (EC) No 1907/2006

# **CONLOC UV 665 FARBIG**

Revision date: 03.05.2023

Product code: 740665613

Page 7 of 12

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
5888-33-5	Isobornyl acrylate			•	•			
	oral	LD50 mg/kg	4350	rat				
	dermal	LD50 mg/kg	> 3000	rabbit				
868-77-9	2-hydroxyethyl methacry	late						
	oral	LD50 mg/kg	5050	Rat				
7473-98-5	2-Hydroxy-2-methylprop	iophenone						
	oral	LD50 mg/kg	1694	rat				
	dermal	LD50 mg/kg	6929	rat	OECD Test Guideline 402			
79-10-7	Acrylsäure							
	oral	LD50 mg/kg	1500	rat				
	dermal	LD50 mg/kg	640	rabbit				
	inhalation (4 h) vapour	LC50	>5,1 mg/l	rat	OECD Test Guideline 403			
	inhalation dust/mist	ATE	1,5 mg/l					
614-45-9	tert-Butylperbenzoat	-						
	oral	LD50 mg/kg	1012	rat				
	inhalation vapour	ATE	11 mg/l					
	inhalation dust/mist	ATE	1,5 mg/l					
110-16-7	maleic acid							
	oral	ATE mg/kg	500					

## Irritation and corrosivity

Serious eye damage/eye irritation Causes skin irritation.

#### Sensitising effects

May cause sensitisation by skin contact.

## Carcinogenic/mutagenic/toxic effects for reproduction

not defined

#### STOT-single exposure not defined

# STOT-repeated exposure

not defined

# Aspiration hazard

## Inhalation may cause respiratory irritation.

# Information on likely routes of exposure

Skin contact, Inhalation

# Specific effects in experiment on an animal

This information is not available.



according to Regulation (EC) No 1907/2006

# **CONLOC UV 665 FARBIG**

Revision date: 03.05.2023

Product code: 740665613

Page 8 of 12

#### **Practical experience**

This information is not available.

# **SECTION 12: Ecological information**

# 12.1. Toxicity

Toxic for Fish. Toxic to aquatic organisms.

Do not empty into drains or the aquatic environment. Leakage of alredy small quantities into the soil hazardous to drinking water

CAS No	Chemical name									
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method			
5888-33-5	Isobornyl acrylate	Isobornyl acrylate								
	Acute fish toxicity	LC50	1,8 mg/l	96 h	Danio rerio (zebra fish)					
	Acute algae toxicity	ErC50	2,7 mg/l	96 h	Pseudokirchneriella subcapitata (green algae)					
	Acute crustacea toxicity	EC50	1,1 mg/l		Daphnia magna (Water flea)					
868-77-9	2-hydroxyethyl methacryl	ate								
	Acute fish toxicity	LC50	227 mg/l	96 h	Pimephales promelas					
7473-98-5	2-Hydroxy-2-methylpropic	phenone		-						
	Acute crustacea toxicity	EC50	119 mg/l	48 h	Toxicity to daphnia	OECD Test Guideline 202				
79-10-7	Acrylsäure									
	Acute algae toxicity	ErC50 mg/l	0,13	72 h	Scenedesmus capricornutum (fresh water algae)					
	Crustacea toxicity	NOEC	19 mg/l	21 d	Daphnia magna (Water flea)					

## 12.2. Persistence and degradability

CAS No	Chemical name						
	Method	Value	d	Source			
	Evaluation						
79-10-7	Acrylsäure						
	OECD Test Guideline 301	81%					
	Easily biodegradable (concerning to the criteria of the OECD); aerobic						

## 12.3. Bioaccumulative potential

This information is not available.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
868-77-9	2-hydroxyethyl methacrylate	0,47
79-10-7	Acrylsäure	0,46

BCF

CAS No	Chemical name	BCF	Species	Source
79-10-7	Acrylsäure	3,16		OECD Test Guideline 107

# 12.4. Mobility in soil

not defined



according to Regulation (EC) No 1907/2006

# **CONLOC UV 665 FARBIG**

Revision date: 03.05.2023

Product code: 740665613

Page 9 of 12

# 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

not defined

#### **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

#### **Disposal recommendations**

Dispose of as special waste in compliance with local and national regulations.

## List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

## List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

#### Contaminated packaging

Dispose of waste according to applicable local, state, and federal regulations.

# SECTION 14: Transport information

Land transport (ADR/RID)	
14.1. UN number or ID number:	UN 3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	(isobornylacrylate, Acrylic acid)
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9
Classification code:	M6
Special Provisions:	274 335 375 601
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	90
Tunnel restriction code:	-
Other applicable information (land transp	port)
The product is not subject to the other (SV 375)	provisions of ADR when packaged in quantities not exceeding 5 I / 5 kg
Marine transport (IMDG)	
14.1. UN number or ID number:	UN 3082



# according to Regulation (EC) No 1907/2006

	Product code: 740665613	Page 10 of 12
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	
	(Isobornyl acrylate, Acrylic acid)	
14.3. Transport hazard class(es):	9	
14.4. Packing group:	III	
Hazard label:	9	
Special Provisions:	274, 335, 969	
Limited quantity:	5 L	
Excepted quantity:	E1	
EmS:	F-A, S-F	
Segregation group:	acids	
Other applicable information (marine transformation) The product may be transported accorrected accorr	ding to IMDG Code, paragraph 2.10.2.7 if it is packed in quantities not	
ir transport (ICAO-TI/IATA-DGR)		
14.1. UN number or ID number:	UN 3082	
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	
	(Isobornyl acrylate, Acrylic acid)	
<u>14.3. Transport hazard class(es):</u>	9	
14.4. Packing group:	III	
Hazard label:	9	
	e e	
Special Provisions:	A97 A158 A197	
Limited quantity Passenger:	30 kg G	
Passenger LQ:	Y964	
Excepted quantity:	E1	
IATA-packing instructions - Passenger:	964	
IATA-max. quantity - Passenger:	450 L	
IATA-packing instructions - Cargo:	964	
IATA-max. quantity - Cargo:	450 L	
Other applicable information (air transp		
	provisions of IATA if it is packed in quantities not exceeding 5 I / 5 kg	
4.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	Yes	
	¥.	

not applicable

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 3, Entry 40, Entry 75



# according to Regulation (EC) No 1907/2006

	according to Regulation (EC) No 1907/2006	
	CONLOC UV 665 FARBIG	
Revision date: 03.05.2023	Product code: 740665613	Page 11 of 12
2004/42/EC (VOC):	0,0%	
National regulatory information		
Water hazard class (D):	2 - obviously hazardous to water	
15.2. Chemical safety assessment		
	for substances in this mixture were not carried out.	
SECTION 16: Other information		
Changes		
_	ges from the previous version in section(s): 6,7,8,9,11,12,16.	
Abbreviations and acronyms	· · · · · · · · · · · · · · · · · · ·	
CLP: Classification, labelling a	nd Packaging	
	on and Authorization of Chemicals	
	stem of Classification, Labelling and Packaging of Chemicals	
UN: United Nations		
CAS: Chemical Abstracts Serv	ice	
DNEL: Derived No Effect Leve		
DMEL: Derived Minimal Effect	Level	
PNEC: Predicted No Effect Co	ncentration	
ATE: Acute toxicity estimate		
LC50: Lethal concentration, 50	%	
LD50: Lethal dose, 50%		
LL50: Lethal loading, 50%		
EL50: Effect loading, 50%		
EC50: Effective Concentration	50%	
ErC50: Effective Concentration	1 50%, growth rate	
NOEC: No Observed Effect Co	-	
BCF: Bio-concentration factor		
PBT: persistent, bioaccumulati	ve, toxic	
vPvB: very persistent, very bio	accumulative	
ADR: Accord européen sur le	ransport des marchandises dangereuses par Route	
(European Agreement concerr	ing the International Carriage of Dangerous Goods by Road)	
RID: Regulations concerning the international carriage of dangerous goods by rail		
ADN: European Agreement co	ncerning the International Carriage of Dangerous Goods by Inland	d Waterways
(Accord européen relatif au tra intérieures)	nsport international des marchandises dangereuses par voies de	navigation
IMDG: International Maritime (	ode for Dangerous Goods	
EmS: Emergency Schedules		
MEAC: Madiaal First Aid Cuid		

MFAG: Medical First Aid Guide

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container

VOC: Volatile Organic Compounds

SVHC: Substance of Very High Concern



according to Regulation (EC) No 1907/2006

# **CONLOC UV 665 FARBIG**

Revision date: 03.05.2023

Product code: 740665613

Page 12 of 12

# Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 1; H410	Calculation method

#### Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H242	Heating may cause a fire.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### **Further Information**

These data describe only the safety requirements for the product(s) and are based on our present knowledge. However, they do not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)