

according to Regulation (EC) No 1907/2006

EGOSILICON 333

Revision date: 02.05.2023

Product code: 333000

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

EGOSILICON 333

Product group:

silicone

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Silicone Sealant

1.3. Details of the supplier of the safety data sheet

Company name:	EGO Dichtstoffwerke GmbH & Co. Bet	riebs KG
Street:	Kaltenbrunn 27	
Place:	D-82467 Garmisch-Partenkirchen	
Telephone: e-mail:	+49 (0)8821 956 90 info@ego.de	Telefax: +49 (0)8821 956 990
Contact person: e-mail: Internet:	Laboratory EGO-Labor@ego.de www.ego.de	Telephone: +49 (0)8821 956 960
1.4. Emergency telephone number:	+49 55119240 (24h/7d) GIZ-Nord, Göttingen Member of EPECs network	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is not classified as hazardous in accordance with Regulation (EC) No 1272/2008.

2.2. Label elements

EUH208

EUH210

Regulation (EC) No 1272/2008

Special labelling of certain mixtures

Contains 3-(Triethoxysilyl)propylamin. May produce an allergic reaction. Safety data sheet available on request.

Additional advice on labelling

The classification corresponds to the current EC listing, but is enhanced by specialised literature data and the Company's own information.

2.3. Other hazards

During polymerization the product releases small quantities of oxime. Prevent vapour buildup by providing adequate ventilation during and after use.

Do not inhale highly-concentrated release products for a longer period of time during polymerization, danger of irritation.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture: Polydimethylsiloxane + curing agents + fillers + auxiliary agents



according to Regulation (EC) No 1907/2006

EGOSILICON 333

Revision date: 02.05.2023

Product code: 333000

Page 2 of 10

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No	1272/2008)		
37859-55-5	2-Pentanone, O,O´,O´´-(methylsilyli	dyne)trioxime		< 5 %
	484-460-1		01-2120004323-76	
	Acute Tox. 4, Eye Irrit. 2; H302 H31	9		
128446-60-6	3-Aminopropyl(methyl)silsesquioxa	n, ethoxy-terminiert		1 - < 5 %
	Flam. Liq. 3, Skin Irrit. 2, Eye Irrit. 2	; H226 H315 H319		
58190-62-8	2-Pentanone, O,O',O"-(ethenylsilyli	dyne)trioxime		1 - < 5 %
	700-810-0		01-2120006148-66	
	Acute Tox. 4, Eye Irrit. 2; H302 H31	9	•	
919-30-2	3-(Triethoxysilyl)propylamin			< 1 %
	213-048-4			
	Acute Tox. 4, Skin Corr. 1B, Eye Da	am. 1, Skin Sens. 1B; H302 H314	H318 H317	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name Quar	
	Specific Conc.	Limits, M-factors and ATE	
37859-55-5	484-460-1	2-Pentanone, O,O´,O´´-(methylsilylidyne)trioxime	< 5 %
	dermal: LD50 -	= >1782 mg/kg; oral: LD50 = 1234 mg/kg	
58190-62-8	700-810-0	2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime	1 - < 5 %
	oral: LD50 = <	2000 mg/kg	
919-30-2	213-048-4	3-(Triethoxysilyl)propylamin	< 1 %
	dermal: LD50 =	= 4076 mg/kg; oral: LD50 = 2660 mg/kg	

Further Information

The light color settings of this product contain titanium dioxide. Pay attention to proper use. See further information in sections 6.1 and 7.1.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

During polymerization the product releases small quantities of oxime. Ensure adequate ventilation, especially in confined areas. Do not breath vapour.

If you feel unwell, seek medical advice (show the label where possible).

After inhalation

Move to fresh air in case of accidental inhalation of vapours.

After contact with skin

Remove mechanically (e.g. dab away using wadding or cellulose material) then thoroughly wash the affected skin with a mild cleanser and water.

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

If a person feels unwell or symptoms of skin irritation appear, consult a physician.

After contact with eyes

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

After ingestion

Rinse mouth. If swallowed, seek medical advice immediately and show this container or label.



according to Regulation (EC) No 1907/2006

EGOSILICON 333

Revision date: 02.05.2023

Product code: 333000

Page 3 of 10

4.2. Most important symptoms and effects, both acute and delayed

Hitherto no symtoms known.

4.3. Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray, Dry powder, Sand, Foam, Carbon dioxide (CO2).

Unsuitable extinguishing media

High volume water jet

5.2. Special hazards arising from the substance or mixture

In the event of fire and/or explosion do not breathe fumes.

Combustion may provoke smoke emission. Hazardous decomposition products formed under fire conditions.

5.3. Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ensure adequate ventilation. Avoid contact with skin and eyes. Do not breath vapour. Use personal protective equipment.

If the dried product is removed mechanically, then respirable titanium dioxide particles can be atomized. A fine dust mask FFP3 (EN 149) must therefore be worn to protect the respiratory tract.

For non-emergency personnel

Remove from all sources of ignition. Provide adequate ventilation. Wear personal protection equipment.

For emergency responders

Wear personal protection equipment.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

For containment

Cover the sewers.

For cleaning up

Contaminated surfaces will be extremely slippery. Use mechanical handling equipment. Dispose of in accordance with local regulations.

To clean the floor and all object contaminated by this material, use Solvent . Cleaning with white-spirit possible.

Other information

Ensure adequate ventilation.

6.4. Reference to other sections

See also section 7, 8, 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice.

Use ventilation adequate to keep exposures below recommended exposure limits. See the safety datasheet. see chapter 8

When using, do not eat, drink or smoke.





according to Regulation (EC) No 1907/2006

EGOSILICON 333

Revision date: 02.05.2023

Product code: 333000

Page 4 of 10

Wash hands before breaks and at the end of workday.

A fine dust mask FFP 3 (EN 149) must be worn when removing dried product residues.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Handle in accordance with good industrial hygiene and safety practice. When using, do not eat, drink or smoke. Avoid contact with the skin and the eyes. Wash hands before breaks and at the end of workday.

Further information on handling

Avoid contact with skin, eyes and clothing.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

None known.

Hints on joint storage

Keep away from food, drink and animal feeding stuffs.

Further information on storage conditions

Keep containers tightly closed in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

Silicone Sealant/adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Name of agent			
DNEL type		Exposure route	Effect	Value
37859-55-5	2-Pentanone, O,O´,O´´-(methylsilylidyne)trioxime			
Worker DNEL	, long-term	inhalation	systemic	1,164 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,165 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,287 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0,0825 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,0825 mg/kg bw/day

PNEC values

CAS No	Name of agent			
Environmental	compartment	Value		
37859-55-5	2-Pentanone, O,O´,O´´-(methylsilylidyne)trioxime			
Freshwater 0,1 mg/l		0,1 mg/l		
Marine water 0,01 mg/l		0,01 mg/l		
Freshwater sediment 0,569 mg/k		0,569 mg/kg		
Marine sediment 0,057 mg/k		0,057 mg/kg		
Micro-organisms in sewage treatment plants (STP) 2,15 mg/l		2,15 mg/l		
Soil 0,04422 mg		0,04422 mg/kg		

Additional advice on limit values

To date, no national critical limit values exist.



according to Regulation (EC) No 1907/2006

EGOSILICON 333

Revision date: 02.05.2023

Product code: 333000

Page 5 of 10

8.2. Exposure controls

Individual protection measures, such as personal protective equipment

Eye/face protection

Safety glasses

Hand protection

Chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374. Break through time >= 60 minutes.

The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.

Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin protection

Protective suit

Respiratory protection

Do not breathe gas/vapour.

Prevent vapour buildup by providing adequate ventilation during and after use.

In case of insufficient ventilation wear suitable respiratory equipment.

Repeated or prolonged exposure: Respirator with a vapour filter (EN 141) - ABEK-filter

Thermal hazards

Do not heat the product. Under fire conditions: Flame-resistant clothing Low temperature resistant gloves: not required

Environmental exposure controls

Do not empty into drains or the aquatic environment.

SECTION 9: Physical and chemical properties

9

9.1. Information on basic physic	al and chemical properties		
Physical state:	paste		
Colour:	various		
Odour:	characteristic		
			Test method
Melting point/freezing point:		not applicable	
Boiling point or initial boiling po	int and	not applicable	
boiling range:			
Lower explosion limits:		not applicable	
Upper explosion limits:		not applicable	
Flash point:		not applicable	
Auto-ignition temperature:		> 400 °C	
pH-Value:		neutral	
Water solubility:		insoluble	
Density:		approx. 1,03 g/cm³	
Particle characteristics:		not applicable	
9.2. Other information			
Information with regard to ph	ysical hazard classes		
Explosive properties			
not Explosive.			
Self-ignition temperature			not auto-flamn

not auto-flammable

SECTION 10: Stability and reactivity



according to Regulation (EC) No 1907/2006

EGOSILICON 333

Revision date: 02.05.2023

Product code: 333000

Page 6 of 10

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

moisture.

10.5. Incompatible materials

Reacts with the following substances: humid air and water, Acids, Alkalis (alkalis).

10.6. Hazardous decomposition products

No decomposition if used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

No data is available on the product itself.

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
37859-55-5	2-Pentanone, O,O',O''-(r	nethylsilylidyne)tri	ioxime			
	oral	LD50 123 mg/kg	4	rat		
	dermal	LD50 >17 mg/kg	'82	rat		
58190-62-8	2-Pentanone, O,O',O"-(et	henylsilylidyne)tri	ioxime			
	oral	LD50 <20 mg/kg	000	Rat		
919-30-2	3-(Triethoxysilyl)propylam	nin				
	oral	LD50 266 mg/kg	0		OECD Test Guideline 401	
	dermal	LD50 407 mg/kg	6	rabbit	OECD Test Guideline 402	

Irritation and corrosivity

Vapour during processing may be irritating to the respiratory tract and to the eyes. May cause eye or skin irritation with susceptible persons.

Sensitising effects

Did not cause sensitisation on laboratory animals. (OECD Test Guideline 406)

Carcinogenic/mutagenic/toxic effects for reproduction

No data is available on the product itself.

STOT-single exposure

No data is available on the product itself.

STOT-repeated exposure

No data is available on the product itself.

Aspiration hazard

No data is available on the product itself.

Information on likely routes of exposure

Skin contact



according to Regulation (EC) No 1907/2006

EGOSILICON 333

Revision date: 02.05.2023

Product code: 333000

Page 7 of 10

Additional information on tests

During polymerization the product releases small quantities of oxime. The cured material is odorless and indifferent.

SECTION 12: Ecological information

12.1. Toxicity

No data is available on the product itself.

Ecological injuries are not known or expected under normal use.

CAS No	Chemical name						
	Aquatic toxicity	Dose		h] [d] Species Source	Method		
37859-55-5	2-Pentanone, O,O',O''-(n	nethylsilylid	yne)trioxime				
	Acute fish toxicity	LC50 mg/l	>113	96 h Oncorhynchus mykiss OECD T (rainbow trout) Guideling			
	Acute algae toxicity	ErC50	100 mg/l	72 h Pseudokirchneriella OECD T subcapitata (green Guideling algae)			
	Acute crustacea toxicity	EC50 mg/l	>113	48 h Daphnia magna OECD T (Water flea) Guideline			
	Algae toxicity	NOEC mg/l	21,5	28 d activated sludge Bacteria			
58190-62-8	2-Pentanone, O,O',O"-(ethenylsilylidyne)trioxime						
	Acute fish toxicity	LC50 mg/l	>117	96 h OECD T Guideline			
	Acute algae toxicity	ErC50	103 mg/l	72 h Pseudokirchneriella OECD T subcapitata (green Guideling algae)			
	Acute crustacea toxicity	EC50	117 mg/l	48 h Daphnia magna OECD T (Water flea) Guideline			
	Fish toxicity	NOEC mg/l	>100	Oncorhynchus mykiss (rainbow trout)			
	Algae toxicity	NOEC	37 mg/l	3 d Pseudokirchneriella subcapitata (green algae) OECD Test Guideline 201			

12.2. Persistence and degradability

silicone bio-degradable.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
37859-55-5	2-Pentanone, O,O´,O´´-(methylsilylidyne)trioxime	1,25

12.4. Mobility in soil

The product is insoluble and sinks in water.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. not applicable

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects



according to Regulation (EC) No 1907/2006

EGOSILICON 333

Revision date: 02.05.2023

Product code: 333000

Page 8 of 10

None known.

Further information

Do not empty into drains or the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of as special waste in compliance with local and national regulations.

Contaminated packaging

Empty remaining contents. Can be landfilled or incinerated, when in compliance with local regulations.

SECTION 14: Transport information

Land transport (ADR/RID)

Μ

• • •	
14.1. UN number or ID number:	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	
14.4. Packing group:	
arine transport (IMDG)	
14.1. UN number or ID number:	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	
14.4. Packing group:	

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. no

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: 14.2. UN proper shipping name:

- 14.3. Transport hazard class(es):
- 14.4. Packing group:

Marine pollutant:

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No

EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 40

National regulatory information

Water hazard class (D):

1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes



according to Regulation (EC) No 1907/2006

EGOSILICON 333

Revision date: 02.05.2023

Product code: 333000

Page 9 of 10

This data sheet contains changes from the previous version in section(s): 1,6,8,9,11,16.

Abbreviations and acronyms

CLP: Classification, labelling and Packaging REACH: Registration. Evaluation and Authorization of Chemicals GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals UN. United Nations CAS: Chemical Abstracts Service DNEL: Derived No Effect Level DMEL: Derived Minimal Effect Level PNEC: Predicted No Effect Concentration ATE: Acute toxicity estimate LC50: Lethal concentration, 50% LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50% EC50: Effective Concentration 50% ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration BCF: Bio-concentration factor PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) RID: Regulations concerning the international carriage of dangerous goods by rail ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures) IMDG: International Maritime Code for Dangerous Goods EmS: Emergency Schedules MFAG: Medical First Aid Guide IATA: International Air Transport Association ICAO: International Civil Aviation Organization MARPOL: International Convention for the Prevention of Marine Pollution from Ships IBC: Intermediate Bulk Container VOC: Volatile Organic Compounds SVHC: Substance of Very High Concern

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
EUH208	Contains 3-(Triethoxysilyl)propylamin. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

Further Information

This recommendation is only valid for the product mentioned in the safety data sheet and provided by us and for the application specified by us.

Moreover, national legislation has to be obeyed!

These data describe only the safety requirements for the product(s) and are based on our present knowledge. However, they do not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.





according to Regulation (EC) No 1907/2006

EGOSILICON 333

Revision date: 02.05.2023

Product code: 333000

Page 10 of 10

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)