

Safety Data Sheet

according to Regulation (EC) No 1907/2006

EGOSILICON 360

Revision date: 02.05.2023 Product code: 3360 Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

EGOSILICON 360

Product group: silicone

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Silicone Sealant

1.3. Details of the supplier of the safety data sheet

Company name: EGO Dichtstoffwerke GmbH & Co. Betriebs KG

Street: Kaltenbrunn 27

Place: D-82467 Garmisch-Partenkirchen

Telephone: +49 (0)8821 956 90 Telefax: +49 (0)8821 956 990

e-mail: info@ego.de

Contact person: Laboratory Telephone: +49 (0)8821 956 960

e-mail: EGO-Labor@ego.de

Internet: www.ego.de

1.4. Emergency telephone+49 55119240 (24h/7d)number:GIZ-Nord, Göttingen

Member of EPECs network

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is not classified as hazardous in accordance with Regulation (EC) No 1272/2008.

2.2. Label elements

Regulation (EC) No 1272/2008

Special labelling of certain mixtures

EUH208 Contains the biocide active ingredient "2-octyl-2H-isothiazol-3-one" for protection against

mold. Keep out of the reach of children Contains 2-octyl-2H-isothiazol-3-one, 3

-(Triethoxysilyl)propylamin. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

Additional advice on labelling

The classification corresponds to the current EC listing, but is enhanced by specialised literature data and the Company's own information.

2.3. Other hazards

During polymerization the product releases small quantities of oxime. Prevent vapour buildup by providing adequate ventilation during and after use.

Do not inhale highly-concentrated release products for a longer period of time during polymerization, danger of irritation.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture: Polydimethylsiloxane + curing agents + fillers + auxiliary agents



Safety Data Sheet

according to Regulation (EC) No 1907/2006

EGOSILICON 360

Revision date: 02.05.2023 Product code: 3360 Page 2 of 9

Hazardous components

| CAS No | Chemical name | | | Quantity | | |
|---------------------------------------|---|--|------------------|----------|--|--|
| | EC No | Index No | REACH No | | | |
| | Classification (Regulation (EC) No | ification (Regulation (EC) No 1272/2008) | | | | |
| 37859-55-5 | 2-Pentanone, O,O´,O´´-(methylsilylidyne)trioxime | | | < 5 % | | |
| | 484-460-1 | | 01-2120004323-76 | | | |
| | Acute Tox. 4, Eye Irrit. 2; H302 H319 | | | | | |
| 58190-62-8 | 62-8 2-Pentanone, O,O',O"-(ethenylsilylidyne)trioxime | | | < 2,5 % | | |
| | 700-810-0 | | 01-2120006148-66 | | | |
| Acute Tox. 4, Eye Irrit. 2; H302 H319 | | | | | | |

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

| CAS No | EC No | Chemical name | Quantity | | | | |
|------------|---|--|----------|--|--|--|--|
| | Specific Conc. I | M-factors and ATE | | | | | |
| 37859-55-5 | 484-460-1 | 2-Pentanone, O,O´,O´´-(methylsilylidyne)trioxime | < 5 % | | | | |
| | dermal: LD50 = >1782 mg/kg; oral: LD50 = 1234 mg/kg | | | | | | |
| 58190-62-8 | 700-810-0 | 2-Pentanone, O,O',O"-(ethenylsilylidyne)trioxime | < 2,5 % | | | | |
| | oral: LD50 = <2000 mg/kg | | | | | | |

Further Information

The light color settings of this product contain titanium dioxide. Pay attention to proper use. See further information in sections 6.1 and 7.1.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

During polymerization the product releases small quantities of oxime. Ensure adequate ventilation, especially in confined areas. Do not breath vapour.

If you feel unwell, seek medical advice (show the label where possible).

After inhalation

Move to fresh air in case of accidental inhalation of vapours.

After contact with skin

Remove mechanically (e.g. dab away using wadding or cellulose material) then thoroughly wash the affected skin with a mild cleanser and water.

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

If a person feels unwell or symptoms of skin irritation appear, consult a physician.

After contact with eyes

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

After ingestion

Rinse mouth. If swallowed, seek medical advice immediately and show this container or label.

4.2. Most important symptoms and effects, both acute and delayed

Hitherto no symtoms known.

4.3. Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures

5.1. Extinguishing media



Safety Data Sheet

according to Regulation (EC) No 1907/2006

EGOSILICON 360

Revision date: 02.05.2023 Product code: 3360 Page 3 of 9

Suitable extinguishing media

Water spray, Dry powder, Sand, Foam, Carbon dioxide (CO2).

Unsuitable extinguishing media

High volume water iet

5.2. Special hazards arising from the substance or mixture

In the event of fire and/or explosion do not breathe fumes.

Combustion may provoke smoke emission. Hazardous decomposition products formed under fire conditions.

5.3. Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ensure adequate ventilation. Avoid contact with skin and eyes. Do not breath vapour. Use personal protective equipment.

If the dried product is removed mechanically, then respirable titanium dioxide particles can be atomized. A fine dust mask FFP3 (EN 149) must therefore be worn to protect the respiratory tract.

For non-emergency personnel

Remove from all sources of ignition. Provide adequate ventilation. Wear personal protection equipment.

For emergency responders

Wear personal protection equipment.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

For containment

Cover the sewers.

For cleaning up

Contaminated surfaces will be extremely slippery. Use mechanical handling equipment. Dispose of in accordance with local regulations.

To clean the floor and all object contaminated by this material, use Solvent. Cleaning with white-spirit possible.

Other information

Ensure adequate ventilation.

6.4. Reference to other sections

See also section 7, 8, 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice.

Use ventilation adequate to keep exposures below recommended exposure limits. See the safety datasheet. see chapter 8

When using, do not eat, drink or smoke.

Wash hands before breaks and at the end of workday.

A fine dust mask FFP 3 (EN 149) must be worn when removing dried product residues.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Handle in accordance with good industrial hygiene and safety practice.

When using, do not eat, drink or smoke. Avoid contact with the skin and the eyes. Wash hands before breaks and at the end of workday.

M - en



Safety Data Sheet

according to Regulation (EC) No 1907/2006

EGOSILICON 360

Revision date: 02.05.2023 Product code: 3360 Page 4 of 9

Further information on handling

Avoid contact with skin, eyes and clothing.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

None known.

Hints on joint storage

Keep away from food, drink and animal feeding stuffs.

Further information on storage conditions

Keep containers tightly closed in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

Silicone Sealant/adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

| CAS No | Name of agent | | | | | |
|--------------------------|--|----------------|----------|------------------------|--|--|
| DNEL type | | Exposure route | Effect | Value | | |
| 37859-55-5 | 2-Pentanone, O,O´,O´´-(methylsilylidyne)trioxime | | | | | |
| Worker DNEL | , long-term | inhalation | systemic | 1,164 mg/m³ | | |
| Worker DNEL, long-term | | dermal | systemic | 0,165 mg/kg bw/day | | |
| Consumer DN | NEL, long-term | inhalation | systemic | 0,287 mg/m³ | | |
| Consumer DNEL, long-term | | dermal | systemic | 0,0825 mg/kg bw/day | | |
| Consumer DNEL, long-term | | oral | systemic | 0,0825 mg/kg bw/day | | |

PNEC values

| CAS No | Name of agent | | | | | |
|---------------------------------|--|--|--|--|--|--|
| Environmental compartment Value | | | | | | |
| 37859-55-5 | 2-Pentanone, O,O´,O´´-(methylsilylidyne)trioxime | | | | | |
| Freshwater 0,1 mg/l | | | | | | |
| Marine water 0,01 mg/l | | | | | | |
| Freshwater sediment 0,569 mg/kg | | | | | | |
| Marine sediment 0,057 mg/kg | | | | | | |
| Micro-organisi | 2,15 mg/l | | | | | |
| Soil | Soil | | | | | |

8.2. Exposure controls

Individual protection measures, such as personal protective equipment

Eye/face protection

Safety glasses

Hand protection

Chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374.

Break through time >= 60 minutes.

The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.

Take note of the information given by the producer concerning permeability and break through times, and of



Safety Data Sheet

according to Regulation (EC) No 1907/2006

EGOSILICON 360

Revision date: 02.05.2023 Product code: 3360 Page 5 of 9

special workplace conditions (mechanical strain, duration of contact).

Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin protection

Protective suit

Respiratory protection

Do not breathe gas/vapour.

Prevent vapour buildup by providing adequate ventilation during and after use.

In case of insufficient ventilation wear suitable respiratory equipment.

Repeated or prolonged exposure: Respirator with a vapour filter (EN 141) - ABEK-filter

Thermal hazards

Do not heat the product.

Under fire conditions: Flame-resistant clothing Low temperature resistant gloves: not required

Environmental exposure controls

Do not empty into drains or the aquatic environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: paste Colour: various Odour: characteristic

Test method

Print date: 02.05.2023

Melting point/freezing point: not applicable Boiling point or initial boiling point and not applicable

boiling range:

Lower explosion limits: not applicable Upper explosion limits: not applicable Flash point: not applicable > 400 °C Auto-ignition temperature: pH-Value: neutral Water solubility: insoluble Density: approx. 1,02 - 1,2 g/cm3 Particle characteristics: not applicable

9.2. Other information

Information with regard to physical hazard classes

Explosive properties not Explosive.

Self-ignition temperature not auto-flammable

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

moisture.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

EGOSILICON 360

Revision date: 02.05.2023 Product code: 3360 Page 6 of 9

10.5. Incompatible materials

Reacts with the following substances: humid air and water, Acids, Alkalis (alkalis).

10.6. Hazardous decomposition products

No decomposition if used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

No data is available on the product itself.

| CAS No | Chemical name | | | | | | |
|------------|--|---------------------|---------|--------|--------|--|--|
| | Exposure route | Dose | Species | Source | Method | | |
| 37859-55-5 | 2-Pentanone, O,O´,O´´-(methylsilylidyne)trioxime | | | | | | |
| | oral | LD50 1234 mg/kg | rat | | | | |
| | dermal | LD50 >1782 mg/kg | rat | | | | |
| 58190-62-8 | 2-Pentanone, O,O',O"-(ethenylsilylidyne)trioxime | | | | | | |
| | oral | LD50 <2000 mg/kg | Rat | | | | |

Irritation and corrosivity

Vapour during processing may be irritating to the respiratory tract and to the eyes.

May cause eye or skin irritation with susceptible persons.

Sensitising effects

Did not cause sensitisation on laboratory animals. (OECD Test Guideline 406)

Carcinogenic/mutagenic/toxic effects for reproduction

No data is available on the product itself.

STOT-single exposure

No data is available on the product itself.

STOT-repeated exposure

No data is available on the product itself.

Aspiration hazard

No data is available on the product itself.

Information on likely routes of exposure

Skin contact

Additional information on tests

During polymerization the product releases small quantities of oxime.

The cured material is odorless and indifferent.

11.2. Information on other hazards

Further information

Health injuries are not known or expected under normal use.

Do not inhale highly-concentrated release products for a longer period of time during polymerization, danger of irritation

SECTION 12: Ecological information

12.1. Toxicity

No data is available on the product itself.

Ecological injuries are not known or expected under normal use.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

EGOSILICON 360

Revision date: 02.05.2023 Product code: 3360 Page 7 of 9

| CAS No | Chemical name | | | | | | |
|------------|--|--|----------|-----------|--|----------------------------|--------|
| | Aquatic toxicity | Dose | | [h] [d] | Species | Source | Method |
| 37859-55-5 | 2-Pentanone, O,O´,O´´-(methylsilylidyne)trioxime | | | | | | |
| | Acute fish toxicity | LC50 mg/l | >113 | 96 h | Oncorhynchus mykiss (rainbow trout) | OECD Test Guideline 203 | |
| | Acute algae toxicity | ErC50 | 100 mg/l | 72 h | Pseudokirchneriella subcapitata (green algae) | OECD Test Guideline 201 | |
| | Acute crustacea toxicity | EC50 mg/l | >113 | | Daphnia magna (Water flea) | OECD Test Guideline 202 | |
| | Algae toxicity | NOEC mg/l | 21,5 | | activated sludge Bacteria | | |
| 58190-62-8 | 2-Pentanone, O,O',O"-(et | 2-Pentanone, O,O',O"-(ethenylsilylidyne)trioxime | | | | | |
| | Acute fish toxicity | LC50 mg/l | >117 | 96 h | | OECD Test Guideline 203 | |
| | Acute algae toxicity | ErC50 | 103 mg/l | 72 h | Pseudokirchneriella subcapitata (green algae) | OECD Test Guideline 201 | |
| | Acute crustacea toxicity | EC50 | 117 mg/l | | Daphnia magna (Water flea) | OECD Test Guideline 202 | |
| | Fish toxicity | NOEC mg/l | >100 | | Oncorhynchus mykiss (rainbow trout) | | |
| | Algae toxicity | NOEC | 37 mg/l | | Pseudokirchneriella subcapitata (green algae) OECD Test Guideline 201 | | |

12.2. Persistence and degradability

silicone bio-degradable.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely.

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|------------|--|---------|
| 37859-55-5 | 2-Pentanone, O,O´,O´´-(methylsilylidyne)trioxime | 1,25 |

12.4. Mobility in soil

The product is insoluble and sinks in water.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. not applicable

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

None known.

Further information

Do not empty into drains or the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods



Safety Data Sheet

according to Regulation (EC) No 1907/2006

EGOSILICON 360

Revision date: 02.05.2023 Product code: 3360 Page 8 of 9

Disposal recommendations

Dispose of as special waste in compliance with local and national regulations.

Contaminated packaging

Empty remaining contents. Can be landfilled or incinerated, when in compliance with local regulations.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Marine pollutant:

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,6,7,8,9,11,16.

Abbreviations and acronyms

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate



Safety Data Sheet

according to Regulation (EC) No 1907/2006

EGOSILICON 360

Revision date: 02.05.2023 Product code: 3360 Page 9 of 9

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules MFAG: Medical First Aid Guide

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds
SVHC: Substance of Very High Concern

Relevant H and EUH statements (number and full text)

H302 Harmful if swallowed.

H319 Causes serious eye irritation.

EUH208 Contains the biocide active ingredient "2-octyl-2H-isothiazol-3-one" for protection against

mold. Keep out of the reach of children Contains 2-octyl-2H-isothiazol-3-one, 3

-(Triethoxysilyl)propylamin. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

Further Information

This recommendation is only valid for the product mentioned in the safety data sheet and provided by us and for the application specified by us.

Moreover, national legislation has to be obeyed!

These data describe only the safety requirements for the product(s) and are based on our present knowledge. However, they do not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)