

EGO Dichtstoffwerke GmbH & Co. Betriebs KG

Safety Data Sheet

according to UK REACH Regulation

EGOSILICON 365 matt

Revision date: 06.10.2022 Product code: 337142 Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

EGOSILICON 365 matt

Product group: Silicone

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Silicone Sealant

1.3. Details of the supplier of the safety data sheet

Company name: EGO Dichtstoffwerke GmbH & Co. Betriebs KG

Street: Kaltenbrunn 27

Place: D-82467 Garmisch-Partenkirchen

Telephone: +49 (0)8821 956 90 Telefax: +49 (0)8821 956 990

e-mail: info@ego.de

Contact person: Laboratory Telephone: +49 (0)8821 956 960

e-mail: EGO-Labor@ego.de

Internet: www.ego.de

1.4. Emergency telephone+49 55119240 (24h/7d)number:GIZ-Nord, Göttingen

Member of EPECs network

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

2.2. Label elements

GB CLP Regulation

Special labelling of certain mixtures

EUH208 Contains the biocide active ingredient "2-octyl-2H-isothiazol-3-one" for protection against

mold. Keep out of the reach of children Contains 2-octyl-2H-isothiazol-3-one. May produce

an allergic reaction.

EUH210 Safety data sheet available on request.

Additional advice on labelling

The classification corresponds to the current EC listing, but is enhanced by specialised literature data and the Company's own information.

2.3. Other hazards

During polymerization the product releases small quantities of oxime. Prevent vapour buildup by providing adequate ventilation during and after use.

Do not inhale highly-concentrated release products for a longer period of time during polymerization, danger of irritation.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture: Polydimethylsiloxane + curing agents + fillers + auxiliary agents





according to UK REACH Regulation

EGOSILICON 365 matt

Revision date: 06.10.2022 Product code: 337142 Page 2 of 9

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (GB CLP Regulation))	·		
37859-55-5	2-Pentanone, O,O´,O´´-(methylsilylidyne)trioxime				
	484-460-1		01-2120004323-76		
	Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2; H312 H302 H319				
58190-62-8	2-Pentanone, O,O',O"-(ethenylsilyli	< 2,5 %			
	700-810-0		01-2120006148-66		
	Acute Tox. 4, Acute Tox. 4, Eye Irri				
540-97-6	Dodecamethylcyclohexasiloxane				
	208-762-8				
541-02-6	Decamethylcyclopentasiloxane	< 1 %			
	208-764-9				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits. M-factors and ATE

CAS No	EC No	Chemical name	Quantity		
	Specific Conc.	Limits, M-factors and ATE			
37859-55-5	484-460-1	2-Pentanone, O,O´,O´´-(methylsilylidyne)trioxime	< 5 %		
	dermal: LD50 = >1782 mg/kg; oral: LD50 = 1234 mg/kg				
58190-62-8	700-810-0	2-Pentanone, O,O',O"-(ethenylsilylidyne)trioxime	< 2,5 %		
	dermal: ATE =	1100 mg/kg; oral: LD50 = <2000 mg/kg			

Further Information

The product contains the following substance of very high concern (SVHC) candidate (s): dodecamethylcyclohexasiloxane, content [%]> = 0.1 - <0.3; Reason for inclusion: Persistent, bioaccumulative and toxic (Article 57d) Very persistent and very bioaccumulative (Article 57e); Decamethylcyclopentasiloxane, content [%]> = 0.1 - <0.3; Reason for inclusion: Persistent, bioaccumulative and toxic (Article 57d) Very persistent and very bioaccumulative (Article 57e)

The light color settings of this product contain titanium dioxide. Pay attention to proper use. See further information in sections 6.1 and 7.1.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

During polymerization the product releases small quantities of oxime. Ensure adequate ventilation, especially in confined areas. Do not breath vapour.

If you feel unwell, seek medical advice (show the label where possible).

After inhalation

Move to fresh air in case of accidental inhalation of vapours.

After contact with skin

Remove mechanically (e.g. dab away using wadding or cellulose material) then thoroughly wash the affected skin with a mild cleanser and water.

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

If a person feels unwell or symptoms of skin irritation appear, consult a physician.





according to UK REACH Regulation

EGOSILICON 365 matt

Revision date: 06.10.2022 Product code: 337142 Page 3 of 9

After contact with eyes

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

After indestion

Rinse mouth. If swallowed, seek medical advice immediately and show this container or label.

4.2. Most important symptoms and effects, both acute and delayed

Hitherto no symtoms known.

4.3. Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray, Dry powder, Sand, Foam, Carbon dioxide (CO2).

Unsuitable extinguishing media

High volume water jet

5.2. Special hazards arising from the substance or mixture

In the event of fire and/or explosion do not breathe fumes.

Combustion may provoke smoke emission. Hazardous decomposition products formed under fire conditions.

5.3. Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ensure adequate ventilation. Avoid contact with skin and eyes. Do not breath vapour. Use personal protective equipment.

If the dried product is removed mechanically, then respirable titanium dioxide particles can be atomized. A fine dust mask FFP3 (EN 149) must therefore be worn to protect the respiratory tract.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Other information

Use mechanical handling equipment. Contaminated surfaces will be extremely slippery.

To clean the floor and all object contaminated by this material, use Solvent . Cleaning with white-spirit possible.

6.4. Reference to other sections

See also section 7, 8, 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice.

Use ventilation adequate to keep exposures below recommended exposure limits. See the safety datasheet. see chapter 8

When using, do not eat, drink or smoke.

Wash hands before breaks and at the end of workday.

A fine dust mask FFP 3 (EN 149) must be worn when removing dried product residues.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.





according to UK REACH Regulation

EGOSILICON 365 matt

Revision date: 06.10.2022 Product code: 337142 Page 4 of 9

Advice on general occupational hygiene

Handle in accordance with good industrial hygiene and safety practice.

When using, do not eat, drink or smoke. Avoid contact with the skin and the eyes. Wash hands before breaks and at the end of workday.

Further information on handling

Avoid contact with skin, eyes and clothing.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

None known.

Hints on joint storage

Keep away from food, drink and animal feeding stuffs.

Further information on storage conditions

Keep containers tightly closed in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

Silicone Sealant/adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
37859-55-5	2-Pentanone, O,O´,O´´-(methylsilylidyne)trioxime					
Worker DNEL	, long-term	inhalation	systemic	1,164 mg/m³		
Worker DNEL, long-term		dermal	systemic	0,165 mg/kg bw/day		
Consumer DN	EL, long-term	inhalation	systemic	0,287 mg/m³		
Consumer DNEL, long-term		dermal	systemic	0,0825 mg/kg bw/day		
Consumer DNEL, long-term		oral	systemic	0,0825 mg/kg bw/day		

PNEC values

CAS No	Substance					
Environmental compartment Value						
37859-55-5	2-Pentanone, O,O´,O´´-(methylsilylidyne)trioxime					
Freshwater	Freshwater 0,1 mg/l					
Marine water	0,01 mg/l					
Freshwater sediment 0,569 mg/kg						
Marine sediment 0,05						
Micro-organis	2,15 mg/l					
Soil		0,04422 mg/kg				

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls

Individual protection measures, such as personal protective equipment





according to UK REACH Regulation

EGOSILICON 365 matt

Revision date: 06.10.2022 Product code: 337142 Page 5 of 9

Eye/face protection

Safety glasses

Hand protection

Chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374.

Break through time >= 60 minutes.

The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.

Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin protection

Protective suit

Respiratory protection

Do not breathe gas/vapour.

Prevent vapour buildup by providing adequate ventilation during and after use.

In case of insufficient ventilation wear suitable respiratory equipment.

Repeated or prolonged exposure: Respirator with a vapour filter (EN 141) - ABEK-filter

Environmental exposure controls

Do not empty into drains or the aquatic environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: paste
Colour: various
Odour: characteristic

Test method

Melting point/freezing point:

Boiling point or initial boiling point and

not applicable
not applicable

boiling range:

Lower explosion limits:

Upper explosion limits:

Inot applicable

Plash point:

Auto-ignition temperature:

pH-Value:

Nater solubility:

Density:

approx. 1,4 g/cm³

Explosive properties not Explosive.

Self-ignition temperature not auto-flammable

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

moisture.



EGO Dichtstoffwerke GmbH & Co. Betriebs KG

Safety Data Sheet

according to UK REACH Regulation

EGOSILICON 365 matt

Revision date: 06.10.2022 Product code: 337142 Page 6 of 9

10.5. Incompatible materials

Reacts with the following substances: humid air and water, Acids, Alkalis (alkalis).

10.6. Hazardous decomposition products

No decomposition if used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

No data is available on the product itself.

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
37859-55-5	2-Pentanone, O,O´,O´´-(methylsilylidyne)trioxime					
	oral	LD50 1 mg/kg	1234	rat		
	dermal	LD50 > mg/kg	>1782	rat		
58190-62-8	2-Pentanone, O,O',O"-(ethenylsilylidyne)trioxime					
	oral	LD50 < mg/kg	<2000	Rat		
	dermal		1100			

Irritation and corrosivity

Vapour during processing may be irritating to the respiratory tract and to the eyes.

May cause eye or skin irritation with susceptible persons.

Sensitising effects

Did not cause sensitisation on laboratory animals. (OECD Test Guideline 406)

Carcinogenic/mutagenic/toxic effects for reproduction

No data is available on the product itself.

STOT-single exposure

No data is available on the product itself.

STOT-repeated exposure

No data is available on the product itself.

Aspiration hazard

No data is available on the product itself.

Additional information on tests

During polymerization the product releases small quantities of oxime.

The cured material is odorless and indifferent.

SECTION 12: Ecological information

12.1. Toxicity

No data is available on the product itself.

Ecological injuries are not known or expected under normal use.



according to UK REACH Regulation

EGOSILICON 365 matt

Revision date: 06.10.2022 Product code: 337142 Page 7 of 9

CAS No Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
37859-55-5	2-Pentanone, O,O´,O´´-(methylsilylidyne)trioxime						
	Acute fish toxicity	LC50 mg/l	>113	I .	Oncorhynchus mykiss (rainbow trout)	OECD Test Guideline 203	
	Acute algae toxicity	ErC50	100 mg/l		Pseudokirchneriella subcapitata (green algae)	OECD Test Guideline 201	
	Acute crustacea toxicity	EC50 mg/l	>113	48 h	Daphnia magna (Water flea)	OECD Test Guideline 202	
	Algae toxicity	NOEC mg/l	21,5		activated sludge Bacteria		
58190-62-8	2-Pentanone, O,O',O"-(ethenylsilylidyne)trioxime						
	Acute fish toxicity	LC50 mg/l	>117	96 h		OECD Test Guideline 203	
	Acute algae toxicity	ErC50	103 mg/l	72 h	Pseudokirchneriella subcapitata (green algae)	OECD Test Guideline 201	
	Acute crustacea toxicity	EC50	117 mg/l		Daphnia magna (Water flea)	OECD Test Guideline 202	
	Fish toxicity	NOEC mg/l	>100		Oncorhynchus mykiss (rainbow trout)		
	Algae toxicity	NOEC	37 mg/l		Pseudokirchneriella subcapitata (green algae) OECD Test Guideline 201		

12.2. Persistence and degradability

silicone bio-degradable.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
37859-55-5	2-Pentanone, O,O´,O´´-(methylsilylidyne)trioxime	1,25

12.4. Mobility in soil

The product is insoluble and sinks in water.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH. not applicable

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

None known.

Further information

Do not empty into drains or the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods





according to UK REACH Regulation

EGOSILICON 365 matt

Revision date: 06.10.2022 Product code: 337142 Page 8 of 9

Disposal recommendations

Dispose of as special waste in compliance with local and national regulations.

Contaminated packaging

Empty remaining contents. Can be landfilled or incinerated, when in compliance with local regulations.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59): Dodecamethylcyclohexasiloxane; Decamethylcyclopentasiloxane

Restrictions on use (REACH, annex XVII):

Entry 70

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Relevant H and EUH statements (number and full text)

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H319 Causes serious eye irritation.



EGO Dichtstoffwerke GmbH & Co. Betriebs KG

Safety Data Sheet

according to UK REACH Regulation

EGOSILICON 365 matt

Revision date: 06.10.2022 Product code: 337142 Page 9 of 9

EUH208 Contains the biocide active ingredient "2-octyl-2H-isothiazol-3-one" for protection against

mold. Keep out of the reach of children Contains 2-octyl-2H-isothiazol-3-one. May produce

an allergic reaction.

EUH210 Safety data sheet available on request.

Further Information

This recommendation is only valid for the product mentioned in the safety data sheet and provided by us and for the application specified by us.

Moreover, national legislation has to be obeyed!

These data describe only the safety requirements for the product(s) and are based on our present knowledge. However, they do not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)