

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

EGO PRIMER FDF

Revision date: 06.12.2024

Product code: 660__300__

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

EGO PRIMER FDF

Product group: primer

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Primer for Silicone Sealant

1.3. Details of the supplier of the safety data sheet

Company name:	EGO Dichtstoffwerke GmbH & Co. Betriebs KG		
Street:	Kaltenbrunn 27		
Place:	D-82467 Garmisch-Partenkirchen		
Telephone:	+49 (0)8821 956 90	Telefax:	+49 (0)8821 956 990
E-mail:	info@ego.de		
Contact person:	Laboratory	Telephone:	+49 (0)8821 956 960
E-mail:	EGO-Labor@ego.de		
Internet:	www.ego.de		

1.4. Emergency telephone

+49 55119240 (24h/7d)

number:GIZ-Nord, Göttingen
Member of EPECs network**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**Flam. Liq. 2; H225
Asp. Tox. 1; H304
Eye Irrit. 2; H319
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**acetone; propan-2-one; propanone
xylene
ethylbenzene

Signal word: Danger

Pictograms:**Hazard statements**

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
------	--

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

EGO PRIMER FDF

Revision date: 06.12.2024

Product code: 660__300_

Page 2 of 13

P233	Keep container tightly closed.
P243	Take action to prevent static discharges.
P261	Avoid inhalation of vapor.
P280	Wear protective gloves / protective clothing / eye protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

During polymerization the product releases small quantities of ethanol. Ethanol is classified in terms of physical hazards and health hazards. The rate of hydrolysis and thus the relevance for the hazard potential of the product are highly dependent on the specific conditions.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

silicon resin in solvent

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
67-64-1	acetone; propan-2-one; propanone			50 - < 55 %
	200-662-2	606-001-00-8		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
1330-20-7	xylene			5 - < 10 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H226 H332 H312 H315 H319 H335 H373 H304 H412			
100-41-4	ethylbenzene			1 - < 5 %
	202-849-4	601-023-00-4		
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1; H225 H332 H373 H304			
78-10-4	tetraethyl silicate; ethyl silicate			1 - < 5 %
	201-083-8	014-005-00-0		
	Flam. Liq. 3, Acute Tox. 4, Eye Irrit. 2, STOT SE 3; H226 H332 H319 H335			

Full text of H and EUH statements: see section 16.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

EGO PRIMER FDF

Revision date: 06.12.2024

Product code: 660__300__

Page 3 of 13

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
67-64-1	200-662-2	acetone; propan-2-one; propanone	50 - < 55 %
		inhalation: LC50 = 76 mg/l (vapours); dermal: LD50 = 20000 mg/kg; oral: LD50 = 5800 mg/kg	
1330-20-7	215-535-7	xylene	5 - < 10 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg	
100-41-4	202-849-4	ethylbenzene	1 - < 5 %
		inhalation: LC50 = 17,2 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 15400 mg/kg; oral: LD50 = 3500 mg/kg	
78-10-4	201-083-8	tetraethyl silicate; ethyl silicate	1 - < 5 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 5880 mg/kg; oral: LD50 = 6270 mg/kg	

Further Information

This product does not contain any reportable Eu-listed Substances of Very High Concern (SVHC) in a concentration of $\geq 0,1\%$ (Regulation (EC) No 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Move out of dangerous area. Do not leave the victim unattended.
Vapours may cause drowsiness and dizziness.
If symptoms persist, call a physician.

After inhalation

Move to fresh air in case of accidental inhalation of vapours. If you feel unwell, seek medical advice (show the label where possible). Keep patient warm and at rest.

After contact with skin

Take off all contaminated clothing immediately. Wash off with soap and water. For large quantities go immediately under the emergency shower. Get medical attention.

After contact with eyes

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

After ingestion

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Danger of inhalation
When unconscious, do not administer anything through the mouth. Show this safety data sheet to the doctor in attendance.

4.2. Most important symptoms and effects, both acute and delayed

Relevant information can be found in other parts of this section.

4.3. Indication of any immediate medical attention and special treatment needed

Further information on toxicology in Section 11 should be noted.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Sand, Dry powder, Alcohol-resistant foam, Carbon dioxide (CO₂).

Unsuitable extinguishing media

Water

5.2. Special hazards arising from the substance or mixture

In case of fire hazardous combustion gases or vapors possible. Exposure to combustion products can be a health hazard! Hazardous fire products: toxic and very toxic fumes.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

EGO PRIMER FDF

Revision date: 06.12.2024

Product code: 660__300_

Page 4 of 13

5.3. Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

Additional information

Standard procedure for chemical fires.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Use personal protective equipment.

Do not breathe vapours or spray mist. Ensure adequate ventilation, especially in confined areas. Avoid contact with skin and eyes.

Keep away from unprotected people. Keep upwind. Remove all sources of ignition.

For non-emergency personnel

Remove from all sources of ignition. Provide adequate ventilation. Wear personal protection equipment.

For emergency responders

Wear personal protection equipment.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Prevent allover extension (e.g. knocking-down or a boom). Retain and dispose of contaminated wash water.

6.3. Methods and material for containment and cleaning up**For containment**

Cover the sewers.

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Use mechanical handling equipment.

Other information

Do not rinse with water. For small quantities: With liquid-binding material, e.g. Diatomaceous earth, pick up and dispose of properly. Dike larger quantities, pump into suitable containers. Remove any remaining slippery surface with detergent / soap solution or other biodegradable cleaner. Vacuum off vapors.

6.4. Reference to other sections

See also section 8, 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Provide sufficient air exchange and/or exhaust in work rooms. Avoid breathing vapours, mist or gas. Avoid contact with skin, eye and clothing. Avoid exposure to women during early pregnancy.

Advice on protection against fire and explosion

Take measures to prevent the build up of electrostatic charge. Processing may lead to evolution of flammable volatiles. Vapours may form explosive mixtures with air near sources of ignition.

Keep away from sources of ignition - No smoking. Cool endangered containers with water spray.

Advice on general occupational hygiene

When using, do not eat, drink or smoke. Do not breathe vapours or spray mist. Avoid contact with skin and eyes. Wash hands before breaks and at the end of workday.

Keep away from food, drink and animal feeding stuffs.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Keep away from direct sunlight.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

EGO PRIMER FDF

Revision date: 06.12.2024

Product code: 660__300__

Page 5 of 13

Avoid subsoil penetration.

Hints on joint storage

Store in accordance with local regulations.

7.3. Specific end use(s)

Primer for Silicone Sealant

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limit values**

CAS No	Name of agent	ppm	mg/m ³	fib/cm ³	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	
100-41-4	Ethylbenzene	100	442		TWA (8 h)	
		200	884		STEL (15 min)	
78-10-4	Tetraethyl orthosilicate	5	44		TWA (8 h)	
1330-20-7	Xylene, mixed isomers, pure	50	221		TWA (8 h)	
		100	442		STEL (15 min)	

DNEL/DMEL values

CAS No	Name of agent			
DNEL type		Exposure route	Effect	Value
78-10-4	tetraethyl silicate; ethyl silicate			
Worker DNEL, acute		dermal	systemic	12,1 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	12,1 mg/kg bw/day
Worker DNEL, acute		inhalation	systemic	85 mg/m³
Worker DNEL, acute		inhalation	local	85 mg/m³
Worker DNEL, long-term		inhalation	systemic	85 mg/m³
Worker DNEL, long-term		inhalation	local	85 mg/m³
Consumer DNEL, acute		dermal	systemic	8,4 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	8,4 mg/kg bw/day
Consumer DNEL, acute		inhalation	systemic	25 mg/m³
Consumer DNEL, acute		inhalation	local	25 mg/m³
Consumer DNEL, long-term		inhalation	systemic	25 mg/m³
Consumer DNEL, long-term		inhalation	local	25 mg/m³

8.2. Exposure controls**Individual protection measures, such as personal protective equipment****Eye/face protection**

Tightly fitting safety goggles. Provide eye wash at work.

Hand protection

Solvent-resistant gloves (butyl-rubber). Duration of use approx. 10-30 minutes.

Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

EGO PRIMER FDF

Revision date: 06.12.2024

Product code: 660__300__

Page 6 of 13

Skin protection

Long sleeved clothing

Respiratory protection

If inhalation exposure above the workplace exposure limit can not be excluded, appropriate respiratory protective equipment should be used. Suitable respiratory protection: Respirator with full face mask, in accordance with recognized standards such as EN 136. Recommended filter type: Combination filter ABEK-P2 (certain inorganic, organic and acid gases and vapors, ammonia / amines, particles), according to recognized standards such as EN 14387. Wear appropriate respiratory protective equipment and protective clothing when exposed to spray or aerosol. Suitable respiratory protection: Self-contained breathing apparatus, according to recognized standards such as EN 137. In case of long or strong exposure, use breathing apparatus. Suitable respiratory protection: Self-contained breathing apparatus, according to recognized standards such as EN 137. The wearing time limit for respiratory protection as well as instructions of the device manufacturer are to be observed.

Thermal hazards

Do not heat the product.

Under fire conditions: Flame-resistant clothing

Low temperature resistant gloves: not required

Environmental exposure controls

Do not flush into surface water or sanitary sewer system.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	colourless
Odour:	characteristic
Odour threshold:	no data available

Test method

Melting point/freezing point:	no data available
Boiling point or initial boiling point and boiling range:	56 °C
Lower explosion limits:	2,3 vol. %
Upper explosion limits:	13 vol. %
Flash point:	-18 °C
Auto-ignition temperature:	540 °C
pH-Value:	approx. 7
Viscosity / kinematic: (at 25 °C)	1,5 mm ² /s DIN 51562-1
Water solubility: (at 20 °C)	900 g/l
Vapour pressure: (at 20 °C)	233 hPa
Density (at 20 °C):	approx. 0,9 g/cm ³ DIN 51757
Particle characteristics:	not applicable

9.2. Other information**Other safety characteristics**

Viscosity / dynamic: (at 25 °C)	1-2 mPa·s
------------------------------------	-----------

Further Information

Explosion limits for released ethanol: 3,5 - 15 Vol%

SECTION 10: Stability and reactivity

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

EGO PRIMER FDF

Revision date: 06.12.2024

Product code: 660__300_

Page 7 of 13

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Heat, flames and sparks. Exposure to moisture..

10.5. Incompatible materials

Water, Acids, Bases.

10.6. Hazardous decomposition products

No decomposition if used as directed. Possible decomposition products in case of hydrolysis are: Ethanol.

The following applies for the silicon portion which is present in substance: Measurements have shown that a small amount of formaldehyde is split off by oxidative decomposition at temperatures above about 150 ° C.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

No toxicology information is available.

Acute toxicity estimate (Dermal exposure) > 2000 mg/kg

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 5000 mg/kg; ATE (inhalation vapour) > 50 mg/l; ATE (inhalation dust/mist) > 5 mg/l

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

EGO PRIMER FDF

Revision date: 06.12.2024

Product code: 660__300__

Page 8 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-64-1	acetone; propan-2-one; propanone				
	oral	LD50 mg/kg	5800	Rat	RTECS
	dermal	LD50 mg/kg	20000	Rabbit	IUCLID
	inhalation (4 h) vapour	LC50	76 mg/l	Rat	
1330-20-7	xylene				
	dermal	ATE mg/kg	1100		
	inhalation vapour	ATE	11 mg/l		
	inhalation dust/mist	ATE	1,5 mg/l		
100-41-4	ethylbenzene				
	oral	LD50 mg/kg	3500	Rat	GESTIS
	dermal	LD50 mg/kg	15400	Rabbit	GESTIS
	inhalation (4 h) vapour	LC50	17,2 mg/l	Rat	
	inhalation dust/mist	ATE	1,5 mg/l		
78-10-4	tetraethyl silicate; ethyl silicate				
	oral	LD50 mg/kg	6270	Rat	GESTIS
	dermal	LD50 mg/kg	5880	Rabbit	GESTIS
	inhalation vapour	ATE	11 mg/l		
	inhalation dust/mist	ATE	1,5 mg/l		

Irritation and corrosivity

Causes serious eye irritation.

Sensitising effects

There is no data available for this product.

Carcinogenic/mutagenic/toxic effects for reproduction

There is no data available for this product.

STOT-single exposure

May cause respiratory tract irritation. Vapors may be narcotic.

STOT-repeated exposure

There is no data available for this product.

Aspiration hazard

Literary reference Component xylene, ethylbenzene: Aspiration hazard

Information on likely routes of exposure

Skin contact, Inhalation

11.2. Information on other hazards**Further information**

Harmful by inhalation and in contact with skin.

Irritating to eyes.

Vapours may cause drowsiness and dizziness.

SECTION 12: Ecological information

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

EGO PRIMER FDF

Revision date: 06.12.2024

Product code: 660__300__

Page 9 of 13

12.1. Toxicity

There is no data available for this product.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-64-1	acetone; propan-2-one; propanone					
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss	
	Acute crustacea toxicity	EC50 mg/l	6100	48 h	Daphnia magna	
100-41-4	ethylbenzene					
	Acute algae toxicity	ErC50	3,6 mg/l	96 h		GESTIS

12.2. Persistence and degradability

Polymer component Non-biodegradable. The product can be eliminated from water by abiotic processes, e.g. adsorption on activated sludge.

12.3. Bioaccumulative potential

No data is available on the product itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone; propan-2-one; propanone	-0,24
100-41-4	ethylbenzene	3,15

12.4. Mobility in soil

Polymer component Insoluble in: Water

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

There is no information.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The substance / mixture does not contain any components in amounts of 0,1% or more which according to REACH Article 57 (f) or the delegated regulation (EU) 2017/2100 of the commission or the delegated regulation (EU) 2018/605 have endocrine disrupting properties.

12.7. Other adverse effects

no data available

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Recommendation: Material that can not be recycled, reprocessed or recycled should be disposed of in an approved facility in accordance with national, state and local regulations. Depending on the regulations, waste treatment methods may include, for example, disposal in a landfill or incineration.

For this product, no waste code number according to the European Waste Catalog (AVV) can be specified, since only the intended use by the consumer allows an allocation. The waste code number must be determined within the EU in consultation with the disposal company.

Contaminated packaging

Packaging must be completely emptied (drip-free, free from trickle, spatula-clean). Packaging must preferably

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

EGO PRIMER FDF

Revision date: 06.12.2024

Product code: 660__300_

Page 10 of 13

be reused or recycled in compliance with the applicable local / national regulations. Non-cleanable packaging must be disposed of in the same way as the substance.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Acetone, xylene)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Special Provisions: 274 601
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Marine transport (IMDG)

14.1. UN number or ID number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Acetone, xylene)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Marine pollutant: no
Special Provisions: 274
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-E
Segregation group: ammonium compounds

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Acetone, xylene)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: A3
Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2
IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

EGO PRIMER FDF

Revision date: 06.12.2024

Product code: 660__300_

Page 11 of 13

IATA-max. quantity - Cargo:

60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Relevant information in other sections must be observed.

14.7. Maritime transport in bulk according to IMO instruments

There is no intended bulk transport in tankers.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,3,9,11,14.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

EGO PRIMER FDF

Revision date: 06.12.2024

Product code: 660__300__

Page 12 of 13

Abbreviations and acronyms

Flam. Liq: Flammable liquid
Acute Tox: Acute toxicity
Asp. Tox: Aspiration hazard
Skin Irrit: Skin irritation
Eye Irrit: Eye irritation
STOT SE: Specific target organ toxicity - single exposure
STOT RE: Specific target organ toxicity - repeated exposure
Aquatic Chronic: Chronic aquatic hazard
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
IMDG: International Maritime Code for Dangerous Goods
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds
SVHC: Substance of Very High Concern

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Asp. Tox. 1; H304	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

EGO PRIMER FDF

Revision date: 06.12.2024

Product code: 660__300_

Page 13 of 13

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

These data describe only the safety requirements for the product(s) and are based on our present knowledge. However, they do not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)