

GOBUTYL 243 AUSGLEICHSBAND

is a tolerance-compensating sealing tape based on butyl rubber which is mainly used in load-transmitting applications owing to its excellent sealing properties. It is characterised by good compatibility and adhesion with concrete and metal. Its properties and components make GOBUTYL 243 excellently suited to "sustainable building", and it promises a long-lasting seal.

CHARACTERISTICS

GOBUTYL 243 is characterized by the following properties:

bitumen-compatible · bitumen-free · easy application · good adhesion and compatibility with most known materials · has an insulating effect · high water vapour diffusion impermeability · immediately functional · no water-damaging components · noise-insulating · non-corrosive · non-shrinking · odourless · permanently self-adhesive · physiologically harmless · plastic · resistant to ageing, weathering, UV and long-term · resistant to waste water · self-sealing · solvent-free · waterproof · water-resistant · when used properly and professionally, EGO Butyl has an almost unlimited service life

APPLICATION AREAS

GOBUTYL 243 is suitable for sealing an even, inflexible load transfer between shaft rings during the installation of shafts for ground-laid waste water channels [according to DIN 4034, part 1]. GOBUTYL 243 compensates for unevenness in bearing regions and thus contributes to the prevention of cracks in shaft rings under static and dynamic loads [particularly traffic loads], but nevertheless has additional sealing properties. It is resistant to conventional waste water. The tape does not replace a prescribed shaft ring seal.

Areas of application:

civil engineering · manhole rings · road construction · transportation

APPLICATION NOTES

The sealing surfaces of the concrete body must be stable, even, solid and have no cracks or cavities in order to achieve waterproof sealing with the integrated underground construction tape. For good initial adhesion, the sealing surfaces must still be dry, stable, and free from dust and de-bonding agents. In order to improve the adhesion to the substrate and as an assembly aid, EGO BUTYLPRIMER PRO or EGO BUTYLPRIMER ECO [solvent free] can be used as a primer. For increased adhesion, please refer to the primer table. The adhesion build-up on the substrate is purely physical and can be improved by pressing or rolling on the substrate and increases again over time. The temperature behaviour is typically thermoplastic, i.e. with increasing temperature, a higher stickiness and softer material consistency is achieved. Place the tape on the prepared sealing surface and press it firmly. The butt joints can be slightly overlapped and pressed [self-sealing]. In cold weather, the sealing tape can be heated with warm air. In order to allow the position of the subsequent shaft ring to be corrected, wet the already positioned GOBUTYL 243 with water to prevent the further shaft ring from bonding straight away. The constant pressure due to the intrinsic weight of the shaft rings, etc. causes the tape to deform and create a reliable seal. It is possible to lay two layers between the shaft rings to bridge large tolerance ranges. GOBUTYL 243 is self-sealing and bonds very well with itself if you just lightly press on it with your finger. It is only possible to separate it again by cutting. To do this, you must first wet a sharp knife with water. Simply dab off butyl residues on the substrates or tools with GOBUTYL 243. Impurities that are difficult to dissolve can be removed mechanically, e.g. with a sharp knife moistened with water, and are best dissolved with cleaning petrol. Compatibility with other building materials is only guaranteed with the EGO products recommended for this. Our list of material properties provides you with an overview of all the necessary information and a detailed comparison of our EGO butyl products.

NORMS AND TESTS

GOBUTYL 243 corresponds to the:

Standards according to:

- DIN 4034, Part 1, Para. 3. 10.

IVD-Instruction-Sheets:

- No. 5

Compatibility:

- with bitumen in accordance with DIN EN 1548

SUSTAINABILITY

VOC emission according to:

- AgBB
- French VOC Class A+ and CMR-Regulation

Product verifications:

- LEED Building Design and Construction V4 [2015]
- BNB BN 2015 [quality level 5/5]
- BREEAM International New Construction 2016
- DGNB New Buildings 2018 [quality level 4/4]

Material requirements for QNG / Quality Seal for Sustainable Buildings:

- Adhesives and sealants in interior rooms incl. TGA according to BNB_BN_11.6, Annex 1, Item 8 and QNG-313, Items 4.1, 4.2
- Adhesives and sealants for creating the airtightness of the façade in accordance with BNB_BN_11.6, Annex 1, Item 9 and QNG-313, Item 4.3



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ [très faibles émissions] à C [fortes émissions]

TECHNICAL DATA

Properties	Result	in accordance with
Material Basis	butyl rubber, polyisobutylene (PIB)	
Density	approx. 1.7 g/cm ³	DIN EN ISO 1183-1
Application Temperature	+5 °C to +30 °C	
Service Temperature	-40 °C to +100 °C	
Shore Hardness 00	approx. 85	DIN EN ISO 868
Penetration butyl [150g, 23°C, 5sec]	approx. 17 [0.1 mm]* Butyl 8x30mm	DIN 51580
Compressive Strength	> 0.50 N/mm ²	LAB-01 [based on NF P30-303]
Peel strength butyl	approx. 10 N/25mm*	LAB-06 [based on DIN EN 29862]
UV, weather and long-term resistance of butyl [after 1000 hrs]	very good no crack formation no breaking no reduction of the tack	DIN EN ISO 4892-2:2013
UV resistance [after 200 hours of UV radiation]	very good no crack formation no breaking no reduction of the tack	
Bending resistance of butyl [after 100 hrs at +90°C & 5 hrs at -30°C]	No crack formation No breaking	
Viscosity	stable	DIN EN ISO 7390
Solids Content	> 99 %	DIN EN ISO 10563
Ignition Temperature	> 400 °C	DIN 51794
Building material class	B2, normal flammability Euro class E	DIN 4102 EN 13501-1

*Average values, not intended for specification

AVAILABILITY AND STORAGE

Standard Color	beige			
Standard Dimensions	Thickness x Width	Meters/Roll	Rolls/Box	Meters/Box
	8,0 x 30 mm	3,7	10	37
	Special sizes on request.			
Storage	Rolls can be stored horizontally, dry and protected from dust: ■ 24 months [at +20 °C] Protect against mechanical damage.			

SAFETY INFORMATION

Complies with	Regulation [EC] No 1907/2006 [REACH]
Not hazardous according to	Regulation [EC] No 1272/2008 [CLP]
Not subject to labeling according to	Regulation [EC] No 1272/2008 [CLP]
Safety instructions	see SDS
Disposal instructions	see SDS

For warnings see EC safety data sheet. The above information is the result of thorough research; previous information is hereby invalidated. Check for yourself whether the product is suitable for your purposes. Our possible liability is limited to the value of our product as such. We cannot accept any liability for indirect damage, in particular for the use or unusability of the product. No one is authorized to make recommendations or assurances on our behalf that go beyond the content of our information sheets.