

## EGOFERM MIT VLIES DUO WANDANSCHLUSSBAND

is immediately functional without waiting time and is characterised by simple, uncomplicated processability. EGOFORM MIT VLIES DUO is a self-adhesive, non-shrinking, thermoplastic, butyl rubber-based sealing tape that is non-detachably laminated with a synthetic fabric to reinforce and limit surface tack. With the sealing tape, vapour diffusion-tight sealing of window connection joints on the ROOM SIDE [RS] is possible according to the principle „tighter on the inside than on the outside“. Due to the fact that the fabric can be plastered and painted over, the sealing tape is ideally suited as an invisible sealant in masonry that has been plastered over, especially in the window connection area.

### CHARACTERISTICS

#### This combination results in optimal product properties:

adhesive on both sides with partial fabric lamination · bitumen-free · good adhesion and compatibility with most known materials  
high water vapour diffusion impermeability · insulating non-shrinking · noise-insulating · non-ageing · odourless · paintable armou-  
ring · physiologically harmless · plasterable armouing · plastic · solvent-free · water-proof · water-tight · when used properly and  
professionally, EGO Butyl has an almost unlimited service life

### APPLICATION AREAS

EGOFERM MIT VLIES DUO is suitable for secure, fast and vapour diffusion-tight sealing of window connection joints. Due to the fabric lamination, the sealing tape can be plastered and painted over and can be installed completely concealed without any problems. At the non-laminated section, the sealing tape is adhesive on both sides and can be fitted to the window without any problems.

#### Areas of application:

window

### APPLICATION NOTES

The bonding surfaces must be dry, stable, free of dust and de-bonding agents. On porous substrates such as concrete, plaster, etc., ad-  
hesion can be increased by pre-treatment with EGO BUTYLPRIMER PRO or EGO BUTYLPRIMER ECO [solvent-free]. For increased adhesion,  
please refer to the primer table. The adhesion build-up on the substrate is purely physical and can be improved by pressing or rolling on  
the substrate and increases again over time. The temperature behaviour is typically thermoplastic, i.e. with increasing temperature,  
a stickier and softer material consistency develops. The adhesive zone can be plastered over up to approx. 30 mm with a maximum  
thickness of 8 mm. In case of overlapping joints of the tapes, pre-treat the fabric contact surface with EGO BUTYLPRIMER PRO. Simply  
dab off butyl residues on the substrates or tools with butyl. Impurities that are difficult to dissolve can be removed mechanically, e.g.  
with a sharp knife moistened with water, and are best dissolved with cleaning petrol.

Compatibility with other building materials is only guaranteed with the EGO products recommended for this.

Our list of material properties provides you with an overview of all the necessary information and a detailed comparison of our EGO  
butyl products.

### NORMS AND TESTS

#### EGOFERM MIT VLIES DUO corresponds to the:

##### Standards according to:

- DIN 52452-4, A1/A2 paint compatible
- DIN 52452-4, A3 over-paintable

##### IVD-Instruction-Sheets:

- No. 3-2, 5, 9, 24, 29, 31

##### Compatibility:

- with bitumen in accordance with DIN EN 1548

### SUSTAINABILITY

#### VOC emission according to:

- AgBB
- French VOC Class A+ and CMR-Regulation

#### Product verifications:

- LEED Building Design and Construction V4 [2015]
- BNB BN 2015 [quality level 5/5]
- BREEAM International New Construction 2016
- DGNB New Buildings 2018 [quality level 4/4]

#### Material requirements for QNG / Quality Seal for Sustainable Buildings:

- Adhesives and sealants in interior rooms incl. TGA according to BNB\_BN\_11.6, Annex 1, Item 8 and QNG-313, Items 4.1, 4.2
- Adhesives and sealants for creating the airtightness of the façade in accordance with BNB\_BN\_11.6, Annex 1, Item 9 and QNG-313, Item 4.3



\*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ [très faibles émissions] à C [Fortes émissions]

### TECHNICAL DATA

Product-Properties	Result	in accordance with
Material Basis butyl	butyl rubber, polyisobutylene [PIB]	
Material Basis fleece	synthetic random fleece	

## EGOFERM MIT VLIES DUO WANDANSCHLUSSBAND

### TECHNICAL DATA

Product-Properties	Result	in accordance with
Application Temperature	+5 °C to +30 °C	
Service Temperature	-40 °C to +100 °C	
Viscosity	stable	DIN EN ISO 7390
Solids Content	> 99 %	DIN EN ISO 10563
μ Value	approx. 766000	DIN EN ISO 12572
Sd Value	Sd = μ x d	d = tape thickness in [m]
Building material class	B2, normal flammability	DIN 4102

  

Butyl-Properties	Result	in accordance with
Density	approx. 1.5 g/cm <sup>3</sup>	DIN EN ISO 1183-1
Shore Hardness 00	approx. 45	DIN EN ISO 868
Compressive Strength	> 0.08 N/mm <sup>2</sup>	LAB-01 [based on NF P30-303]
Peel strength	approx. 80 N/25mm*	LAB-06 [based on DIN EN 29862]
Penetration butyl [150g, 23°C, 5 sec]	approx. 57 [0.1mm]* Butyl 30x30mm	DIN 51580
UV, weather and long-term resistance of butyl [after 1000 hrs]	very good no crack formation no breaking no reduction of the tack	DIN EN ISO 4892-2:2013
Bending resistance of butyl [after 100 hrs at +90°C & 5 hrs at -30°C]	No crack formation No breaking	

\*Average values, not intended for specification

### AVAILABILITY AND STORAGE

Standard Color Butyl	grey			
Standard Color Fleece	white			
Standard Dimensions	Thickness x Width	Meters/Roll	Rolls/Box	Meters/Box
	1,5 x 75 mm	25	4	100
	1,5 x 100 mm	25	2	50
	Special sizes on request.			
Storage	Rolls can be stored horizontally, dry and protected from dust: ■ 24 months [at +20°C]  Protect against mechanical damage.			

### SAFETY INFORMATION

Complies with	Regulation [EC] No 1907/2006 [REACH]
Not hazardous according to	Regulation [EC] No 1272/2008 [CLP]
Not subject to labeling according to	Regulation [EC] No 1272/2008 [CLP]
Safety instructions	see SDS
Disposal instructions	see SDS

For warnings see EC safety data sheet. The above information is the result of thorough research; previous information is hereby invalidated. Check for yourself whether the product is suitable for your purposes. Our possible liability is limited to the value of our product as such. We cannot accept any liability for indirect damage, in particular for the use or unusability of the product. No one is authorized to make recommendations or assurances on our behalf that go beyond the content of our information sheets.