

EGOPREN S VORLEGE BAND

is a foamed, cell-closed, weather resistant and plasticizer-free one-sided adhesive PE tape. The laminated PE film serves as a release agent for the adhesive side and this makes fast processing without protective covering possible.

APPLICATION

In order to create spacing when glazing and subsequent application of sealant for ordinary and insulating panes of glass, as well as balustrade elements in the corresponding profiles. The compatibility with Plexiglas is provided for up to a thickness of 5 mm.

INSTRUCTIONS

Adhesion surfaces must be clean, dry and free from dust and substances liable to impair adhesion. Remove the release film and position the tape leaving a joint of at least 5 mm depth for the sealant. Apply the sealant immediately after glazing.

STANDARDS

EGOPREN S complies with the:

IVD data sheets:

- No. 10, 29

Compatibilities:

- EGOPREN S Foam Sealant Strip is compatible with all EGO products. The product is resistant to water and most common chemical products.

SPECIFICATIONS

Properties	Result	in accordance with
Material basis	PE-foam	
Density	0,03 g/cm ³	DIN EN ISO 845
Application Temperature	+2 °C to +30 °C	
Service Temperature	-40 °C to +50 °C	
Compression Set after 25 % compression		
- Decompression after 30 min.	20 %	DIN EN ISO 1856-C
- Decompression after 2 hours	10 %	DIN EN ISO 1856-C
Compression hardness on 25%	38kPa	ISO 844
Thermal conductivity	approx. 0,034 W/mK	ISO 2581
Building Material Class	B2, normally flammable	DIN 4102

AVAILABILITY AND STORAGE

Standard Colour	black, white				
Standard Sizes	Thickness x Width				
	2 x 6 mm	3 x 6 mm			
	2 x 7 mm				
	2 x 8 mm	3 x 8 mm	4 x 8 mm		
	2 x 9 mm	3 x 9 mm	4 x 9 mm	5 x 9 mm *	6 x 9 mm *
	2 x 10 mm	3 x 10 mm	4 x 10 mm	5 x 10 mm *	6 x 10 mm *
	2 x 12 mm	3 x 12 mm	4 x 12 mm	5 x 12 mm *	6 x 12 mm *
	2 x 15 mm	3 x 15 mm			
	2 x 20 mm	3 x 20 mm			
Packaging	All dimensions are available in roll lengths of 10m and 20m. The dimensions marked with * are delivered with a roll length of 10m.				
Storage	Rolls can be stored in a cool, dry place: ▪ 12 months				

SAFETY INFORMATION

Meets Requirements of	REACH Regulation (EC) No. 1907/2006
Not hazardous	According to EC No. 1272/2008 (CLP)
Not subject to Labelling	According to EC No. 1272/2008 (CLP)
Safety Guidelines	See EC safety data sheet
Disposal	See EC safety data sheet

For warnings refer to the Safety Data Sheet. The above information is the result of thorough research; previous information is hereby invalidated. Check for yourself whether the product is suitable for your purposes. Our possible liability is limited to the value of our product as such. We cannot accept any liability for indirect damage, in particular for the application or unusability of the product. No one is authorized to make recommendations or assurances on our behalf that go beyond the content of our information sheets.