

## EGO BLEIVERGLASUNGSKITT

is made from a combination of synthetic resin with vegetable oils and synthetic additives and is suitable for synthetic glazing in lead, brass or light metal.

### APPLICATION AREAS

EGO BLEIVERGLASUNGSKITT is ideal for lead glazing.

#### Areas of application:

Artistic glazing

#### Good adhesion to:

lead · light metal · brass

### APPLICATION NOTES

- ❶ To achieve wind stability and weather resistance of the individual glass panels after the brazing process, the joints between glass and glazing bars have to be filled on both sides with EGO BLEIVERGLASUNGSKITT using a brush or spatula.
- ❷ Contaminations can be removed with chalk or similar products using a brush or cloth.
- ❸ Positioning the glass pane into the frame has to be done in accordance with the directives of the Institut für Fenstertechnik e. V., Rosenheim, Germany.

### TECHNICAL DATA

Properties	Result
Density	approx. 1,8 g/cm <sup>3</sup>
Application Temperature	approx. +5 °C to +30 °C
Service Temperature	approx. -30 °C to +80 °C
Consistency	spreadable
Properties	hardening, adherent, thixotropic
Method of Application	manually with brush or spatula
Rework	with polished putty knife or spatula
Secondary Treatment	overpainting possible

### AVAILABILITY AND STORAGE

Standard Colour	grey
Packaging	<ul style="list-style-type: none"> <li>▪ 9 kg tin bucket</li> <li>▪ Special packaging upon request</li> </ul>
Storage	Store in original packaging in a cool, dry place: <ul style="list-style-type: none"> <li>▪ 12 months</li> </ul>

### SAFETY INSTRUCTIONS

Meets Requirements of	REACH Regulation (EC) No. 1907/2006 and No. 1272/2008 CLP
Labelling	See EC safety data sheet
Safety Guidelines	See EC safety data sheet
Disposal	See EC safety data sheet

For warnings refer to the Safety Data Sheet. The above information is the result of thorough research; previous information is hereby invalidated. Check for yourself whether the product is suitable for your purposes. Our possible liability is limited to the value of our product as such. We cannot accept any liability for indirect damage, in particular for the application or unusability of the product. No one is authorized to make recommendations or assurances on our behalf that go beyond the content of our information sheets.