

EGO BUTYLPRIMER PRO

is a ready-for-use, solvent-based, moisture-resistant bonding agent for porous and nonporous substrates.

PROPERTIES

The product is characterized by the following properties:

easy application · increases the adhesive strength of butyl and bitumen tapes · for absorbent and porous substrates · optimum adhesion to a wide range of substrates · fast flash-off time [10 minutes]

APPLICATION

EGO BUTYLPRIMER PRO is suitable for priming and increasing the adhesive strength of butyl tapes, bitumen tapes or solvent-compatible adhesive tapes on absorbent and porous substrates. Particularly suitable for achieving secure and fast adhesion of EGO butyl tapes to porous materials. Also suited for the pre-treatment of adhesion surfaces in the concrete construction, in roof areas and for connecting joints in the building construction sealed with butyl sealing tapes.

Good adhesion to:

aerated concrete · chipboard · concrete · gypsum boards · masonry · plaster · wood

INSTRUCTIONS

- ① Adhesion surfaces must be dry, clean and free from dust and substances liable to impair adhesion.
 - ② EGO BUTYLPRIMER PRO is applied undiluted, evenly and in a single coat using a brush. Very absorbent substrates may be primed twice.
 - ③ Adapt the width of the primer coat to the width of the butyl sealing tape to be applied afterwards.
 - ④ Drying time depends on the thickness of the primer coat and the ambient temperature and is about 10 minutes at 20 °C. Do not apply the tape before.
 - ⑤ In case of internal applications ensure sufficient ventilation.
- * Notes:
- On slightly damp and very absorbent surfaces EGO BUTYLPRIMER PRO takes longer to dry.
 - Avoid soiling of the primer coat.
 - Own tests or consultation recommended.

SPECIFICATIONS

Properties	Result
Material Basis	Synthetic rubber and organic solvents
Density	approx. 0,75 g/cm ³
Application Temperature	+5 °C to +30 °C
Service Temperature	-20 °C to +80 °C
Viscosity	approx. 150 mPa·s
Solids Content	approx. 20 %
Drying Time	approx. 10 minutes, depending on substrate and ambient temperature
Coverage Rate	approx. 150 to 250 ml/m ² depending on substrate
Cleaning	With EGO REINIGUNGSSPRAY or benzine

AVAILABILITY AND STORAGE

Colour	Yellow to brownish
Packaging	<ul style="list-style-type: none"> ▪ 500 ml can ▪ 5 L tin canister
Storage	Store in original packaging in a cool, dry place: <ul style="list-style-type: none"> ▪ 12 months

SAFETY INSTRUCTIONS

Meets Requirements of	REACH Regulation (EC) No. 1907/2006 and No. 1272/2008 CLP
Labelling	See EC safety data sheet
Safety Guidelines	See EC safety data sheet
Disposal	See EC safety data sheet

For warnings refer to the Safety Data Sheet. The above information is the result of thorough research; previous information is hereby invalidated. Check for yourself whether the product is suitable for your purposes. Our possible liability is limited to the value of our product as such. We cannot accept any liability for indirect damage, in particular for the application or unusability of the product. No one is authorized to make recommendations or assurances on our behalf that go beyond the content of our information sheets.