

EGO UNIVERSALVLIES FENSTERANSCHLUSS

is a highly adhesive fleece foil tape with one adhesive side for sealing of window joints. Thanks to its variable SD value, the tape is suitable for sealing both inside and outside. EGO UNIVERSALVLIES is highly adhesive and can be plastered over or painted. The foil tape is elastic and can also be handled at low temperatures.

APPLICATION AREAS

For inside and outside sealing of window joints in new and old buildings. Suitable for use on all types of window frames and various surfaces on walls.

APPLICATION NOTES

Surfaces for adhesion must be dry and free from dust and release agents and offer sufficient load-bearing capacity. Moisture due to ice or condensation can compromise adhesion. Adhesion on the respective surface must be tested in advance. Gradually pull off the backing paper on the adhesive side, apply EGO UNIVERSALVLIES to the window rear and all sides to be sealed at the window and press on it firmly (for inside and outside sealing). Align the window element, attach it, pull off the remaining backing paper, apply EGO UNIVERSALVLIES at the wall and press on it firmly.

NORMS AND TESTS

EGO UNIVERSALVLIES complies with the:

Standards:

- DIN EN 13501

IVD data sheets:

- No. 9, 29, 35

The following tests were achieved by EGO UNIVERSALVLIES:

Testing:

- Air permeability and watertightness, unaged and after approx. 3 months of outdoor exposure

Federal German Association of the Gypsum Industry:

- Industry group for building plaster: Issue on "Plastering of window joint foil"

TECHNICAL DATA

Properties	Result	In accordance with
Material Basis	PET fleece with acrylic adhesive on one side	
Weight	approx. 280 g/m ²	DIN EN 29073-1
Adhesive weight	approx. 180 g/m ²	DIN EN 29073-1
Thickness	0,5 mm	DIN EN 29073-1
Application Temperature	+5°C to +40°C	
Service Temperature	-40°C to +80°C	
Driving rain impermeability	> 600 Pa	EN 1027
Watertightness	passed	
Sd Value	0,5 m ≤ sd ≤ 12 m	EN 1931 EN 12572
Outdore Exposure/UV	3 months	
Building Material Class	E, normally flammable	EN 13501

AVAILABILITY AND STORAGE

Standard Colour	White			
Standard Dimensions	Width	Meters/Roll	Roll/Box	Meters/Box
	75 mm	25	5	125
	100 mm	25	4	100
	150 mm	25	2	50
Storage	Store rolls horizontally, dry and protected from dust: ▪ 24 months [at +20°C] Protect from mechanical damage.			

EGO UNIVERSALVLIES FENSTERANSCHLUSS

SAFETY INSTRUCTIONS

Meets Requirements of	REACH Regulation (EC) No. 1907/2006
Not hazardous	According to EC No. 1272/2008 (CLP)
Not subject to labelling	According to EC No. 1272/2008 (CLP)
Safety Guidelines	See EC safety data sheet
Disposal	See EC safety data sheet

For warnings refer to the Safety Data Sheet. The above information is the result of thorough research; previous information is hereby invalidated. Check for yourself whether the product is suitable for your purposes. Our possible liability is limited to the value of our product as such. We cannot accept any liability for indirect damage, in particular for the application or unusability of the product. No one is authorized to make recommendations or assurances on our behalf that go beyond the content of our information sheets.